

屋内照明器具特性	
品番 (品名)	N Y M2 0 2 8 5
光源	LED5000_85_42300 ×1 42300.0 lm
管理番号	K0184477 (0) DR 1
B Z 分類	BZ2 / 1.8 / BZ3

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
						室指数	照明率 (X 0 . 0 1)																			
保守率		良 中 否	0 . 8 3	0 . 6	6 7	5 7	5 1	4 6	6 6	5 7	5 0	4 6	6 4	5 6	5 0	4 6	6 2	5 5	5 0	4 6	4 4					
			0 . 8 1	0 . 8	7 6	6 7	6 1	5 6	7 5	6 6	6 0	5 6	7 3	6 5	6 0	5 6	7 0	6 4	5 9	5 6	5 4					
			0 . 7 7	1 . 0	8 2	7 4	6 8	6 3	8 1	7 3	6 7	6 3	7 8	7 1	6 6	6 3	7 6	7 0	6 6	6 2	6 0					
				1 . 2 5	8 7	7 9	7 4	7 0	8 5	7 9	7 3	6 9	8 3	7 7	7 2	6 9	8 1	7 6	7 2	6 8	6 6					
下方投影面積		c m ²	1 . 5	9 0	8 3	7 8	7 4	8 9	8 3	7 8	7 4	8 6	8 1	7 7	7 3	8 4	7 9	7 6	7 3	7 1						
			2 . 0	9 4	8 9	8 4	8 1	9 3	8 8	8 4	8 0	9 0	8 6	8 3	7 9	8 8	8 4	8 1	7 9	7 7						
等価発光面積		c m ²	2 . 5	9 7	9 2	8 9	8 5	9 6	9 1	8 8	8 5	9 3	9 0	8 6	8 4	9 1	8 8	8 5	8 3	8 0						
			3 . 0	9 9	9 5	9 1	8 8	9 8	9 4	9 1	8 8	9 5	9 2	8 9	8 7	9 3	9 0	8 8	8 6	8 3						
H m	1 . 1 0 H m	1 . 1 0 H m	4 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 4	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	8 9	8 7						
			5 . 0	1 0 3	1 0 0	9 8	9 5	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 6	9 5	9 3	9 2	8 9						
			7 . 0	1 0 4	1 0 2	1 0 0	9 9	1 0 3	1 0 1	9 9	9 8	1 0 0	9 9	9 8	9 6	9 8	9 7	9 6	9 5	9 2						
			1 0 . 0	1 0 5	1 0 4	1 0 3	1 0 1	1 0 4	1 0 3	1 0 2	1 0 0	1 0 2	1 0 1	1 0 0	9 9	9 9	9 9	9 8	9 7	9 4						

