

屋内照明器具特性	
品番 (品名)	N Y M2 0 2 7 2
光源	LED5000_85_21300 ×1 21300.0 lm
管理番号	K0184474 (2) DR 1
B Z 分類	BZ1 / 1.4 / BZ2

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 8 3	0 . 6	7 4	6 6	6 1	5 7	7 4	6 6	6 1	5 7	7 2	6 5	6 0	5 7	7 0	6 4	6 0	5 7	5 6
			0 . 8 1	0 . 8	8 2	7 4	6 9	6 5	8 1	7 4	6 9	6 5	7 9	7 2	6 8	6 5	7 7	7 2	6 8	6 5	6 3
			1 . 0	8 6	7 9	7 4	7 1	8 5	7 9	7 4	7 0	8 3	7 7	7 3	7 0	8 1	7 6	7 3	7 0	6 8	
			0 . 7 7	1 . 2 5	9 0	8 4	7 9	7 6	8 9	8 3	7 9	7 5	8 7	8 2	7 8	7 5	8 5	8 1	7 7	7 4	7 3
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	9 3	8 7	8 3	7 9	9 2	8 7	8 2	7 9	8 9	8 5	8 1	7 8	8 7	8 4	8 0	7 8	7 6	
			2 . 0	9 7	9 2	8 8	8 5	9 5	9 1	8 7	8 4	9 3	8 9	8 6	8 4	9 1	8 8	8 5	8 3	8 1	
			2 . 5	9 9	9 5	9 1	8 8	9 7	9 4	9 1	8 8	9 5	9 2	8 9	8 7	9 3	9 0	8 8	8 6	8 4	
取付 高さ	器具間隔最大限		3 . 0	1 0 0	9 7	9 4	9 1	9 9	9 6	9 3	9 1	9 7	9 4	9 1	8 9	9 4	9 2	9 0	8 8	8 6	
	横方向 (A)	縦方向 (B)	4 . 0	1 0 2	9 9	9 7	9 5	1 0 1	9 8	9 6	9 4	9 8	9 6	9 4	9 3	9 6	9 4	9 3	9 1	8 9	
H m	0 . 8 3 H m	0 . 8 3 H m	5 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 5	9 7	9 6	9 5	9 3	9 1	
			7 . 0	1 0 5	1 0 3	1 0 1	1 0 0	1 0 3	1 0 2	1 0 0	9 9	1 0 1	1 0 0	9 9	9 7	9 9	9 8	9 7	9 6	9 3	
			1 0 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 5	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 8	9 5	

