

| 屋内照明器具特性 |                                   |
|----------|-----------------------------------|
| 品番 (品名)  | NTN88006BK                        |
| 光源       | LLD40402CQ1 (KAKUSAN) ×1 860.0 lm |
| 管理番号     | K0183945 (0) DR1                  |
| BZ分類     | BZ2                               |

| 器具効率             |          | 57 %            | 反射率             | 天井   | 80 %          |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|------------------|----------|-----------------|-----------------|------|---------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|                  |          |                 |                 | 壁    | 70            | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|                  |          |                 |                 | 床    | 10 %          |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|                  |          |                 |                 | 室指数  | 照明率 ( X0.01 ) |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    | Z   |
| 保守率              |          | 良<br>中<br>否     | 0.67            | 0.6  | 38            | 33 | 29 | 26 | 38   | 32 | 29 | 26 | 36   | 32 | 29 | 26 | 35   | 31 | 28 | 26 | 25  |
|                  |          |                 | 0.63            | 0.8  | 44            | 39 | 35 | 33 | 43   | 38 | 35 | 33 | 42   | 38 | 35 | 33 | 41   | 37 | 35 | 33 | 32  |
|                  |          |                 | 0.56            | 1.0  | 47            | 43 | 40 | 37 | 47   | 43 | 40 | 37 | 45   | 42 | 39 | 37 | 44   | 41 | 39 | 37 | 36  |
|                  |          |                 |                 | 1.25 | 50            | 46 | 44 | 41 | 50   | 46 | 43 | 41 | 48   | 45 | 43 | 41 | 47   | 44 | 42 | 41 | 40  |
| 下方投影面積<br>等価発光面積 |          | cm <sup>2</sup> |                 | 1.5  | 52            | 49 | 46 | 44 | 51   | 48 | 46 | 44 | 50   | 47 | 45 | 43 | 49   | 47 | 45 | 43 | 42  |
|                  |          |                 | cm <sup>2</sup> | 2.0  | 55            | 52 | 50 | 48 | 54   | 51 | 49 | 48 | 53   | 50 | 49 | 47 | 51   | 49 | 48 | 47 | 45  |
| 取付<br>高さ         | 器具間隔最大限  |                 |                 | 2.5  | 56            | 54 | 52 | 50 | 55   | 53 | 51 | 50 | 54   | 52 | 51 | 49 | 53   | 51 | 50 | 49 | 48  |
|                  | 横方向 (A)  | 縦方向 (B)         |                 | 3.0  | 57            | 55 | 53 | 52 | 56   | 54 | 53 | 52 | 55   | 53 | 52 | 51 | 54   | 52 | 51 | 50 | 49  |
| H m              | 1.15 H m | 1.15 H m        |                 | 4.0  | 58            | 57 | 55 | 54 | 57   | 56 | 55 | 54 | 56   | 55 | 54 | 53 | 55   | 54 | 53 | 52 | 51  |
|                  |          |                 |                 | 5.0  | 59            | 58 | 56 | 55 | 58   | 57 | 56 | 55 | 57   | 56 | 55 | 54 | 56   | 55 | 54 | 53 | 52  |
|                  |          |                 |                 | 7.0  | 60            | 59 | 58 | 57 | 59   | 58 | 57 | 57 | 58   | 57 | 56 | 56 | 56   | 56 | 55 | 55 | 53  |
|                  |          |                 |                 | 10.0 | 60            | 60 | 59 | 58 | 60   | 59 | 58 | 58 | 58   | 58 | 57 | 57 | 57   | 57 | 56 | 56 | 54  |

