

屋内照明器具特性	
品番 (品名)	NTN88006WK
光源	LLD4000LCE1 ×1 845.0 lm
管理番号	K0175549 (0) DR 1
BZ分類	BZ4/0.7/BZ3

器具効率		83 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.67	0.6	51	41	35	31	50	41	35	31	48	40	35	31	46	39	34	31	29				
			0.63	0.8	59	51	45	41	58	50	45	41	56	49	44	40	54	48	44	40	39				
			0.56	1.0	65	57	52	48	64	57	51	47	62	55	51	47	60	54	50	47	45				
				1.25	70	63	58	54	69	62	57	54	66	61	57	53	64	60	56	53	51				
下方投影面積 等価発光面積		cm ² cm ²		1.5	73	67	62	58	72	66	62	58	69	65	61	58	67	63	60	57	55				
				2.0	77	72	68	65	76	71	67	64	74	70	66	64	72	68	65	63	61				
				2.5	80	75	72	69	78	75	71	68	76	73	70	68	74	71	69	67	65				
				3.0	81	78	75	72	80	77	74	71	78	75	73	70	76	74	71	70	68				
H _m	1.25H _m	1.25H _m		4.0	83	81	78	76	82	80	77	75	80	78	76	74	78	76	75	73	71				
				5.0	85	82	80	78	84	81	79	78	81	80	78	76	79	78	77	75	73				
				7.0	86	84	83	81	85	83	82	81	83	82	80	79	81	80	79	78	76				
				10.0	87	86	85	84	86	85	84	83	84	83	82	81	82	81	81	80	78				

