

屋内照明器具特性	
品番 (品名)	NTN88006WK
光源	LLD4000LCS1 ×1 830.0 lm
管理番号	K0181856 (0) DR 1
BZ分類	BZ4/0.7/BZ3

器具効率		76 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) ZCM															
保守率		良 中 否	0.67	0.6	46	38	33	29	46	38	32	29	44	37	32	29	42	36	32	28	27	
			0.63	0.8	54	46	41	37	53	46	41	37	51	45	40	37	49	44	40	37	35	
			0.56	1.0	59	52	47	43	58	51	46	43	56	50	46	42	54	49	45	42	41	
				1.25	63	57	52	48	62	56	52	48	60	55	51	48	58	54	50	47	46	
下方投影面積		cm ²	1.5	66	60	56	52	65	60	56	52	63	58	55	52	61	57	54	51	50		
等価発光面積				cm ²	2.0	70	65	61	58	69	65	61	58	67	63	60	57	65	62	59	57	55
取付高さ	器具間隔最大限 <td>2.5</td> <td>72</td> <td>68</td> <td>65</td> <td>62</td> <td>71</td> <td>68</td> <td>64</td> <td>62</td> <td>69</td> <td>66</td> <td>63</td> <td>61</td> <td>67</td> <td>65</td> <td>62</td> <td>60</td> <td>59</td>				2.5	72	68	65	62	71	68	64	62	69	66	63	61	67	65	62	60	59
	横方向 (A)		縦方向 (B)		3.0	74	71	68	65	73	70	67	65	71	68	66	64	69	67	65	63	61
H m	1.20 H m	1.20 H m	4.0	76	73	71	69	75	73	70	68	73	71	69	67	71	69	68	66	64		
			5.0	77	75	73	71	76	74	72	71	74	73	71	70	72	71	70	68	66		
			7.0	79	77	76	74	78	76	75	73	76	75	73	72	74	73	72	71	69		
			10.0	80	79	77	76	79	78	77	76	77	76	75	74	75	74	74	73	71		

