

屋内照明器具特性	
品番 (品名)	XNW2 5 6 2 WN
光源	LED5000_85_2340 x1 2340.0 lm
管理番号	K0183311 (0) DB 1
BZ分類	BZ1

器具効率		100 % 上方光束 0 % 下方光束	反 射 率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
		100 %	室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.81	0.6	85	79	75	72	84	78	75	72	83	78	74	72	81	77	74	72	71	
			0.77	0.8	91	85	82	79	90	85	81	79	88	84	81	79	87	83	81	78	77	
			0.68	1.0	94	90	86	84	93	89	86	84	92	88	85	83	90	87	85	83	82	
下方投影面積		c m ²	1.25	97	93	90	88	96	92	90	87	95	91	89	87	93	90	88	86	85		
等価発光面積			c m ²	1.5	99	95	93	90	98	95	92	90	96	93	91	89	95	92	90	89	87	
			2.0	101	98	96	94	100	98	95	94	99	96	94	93	97	95	93	92	90		
取付	器具間隔最大限		2.5	103	100	98	97	102	100	98	96	100	98	96	95	98	96	95	94	92		
高さ	横方向 (A)		縦方向 (B)	3.0	104	102	100	98	103	101	99	98	101	99	98	96	99	98	96	95	93	
H m	0.79 H m			0.79 H m	4.0	105	103	102	100	104	102	101	100	102	101	99	98	100	99	98	97	95
			5.0	106	104	103	102	105	103	102	101	102	101	101	100	101	100	99	98	96		
			7.0	107	105	105	104	105	104	104	103	103	102	102	101	101	101	100	99	97		
			10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	100	98		

