

屋内照明器具特性

品番 (品名) **LGB16778**

光源 **LLD2020LCE1 x1** **460.0 l m**

管理番号 **K0175674 (1) DR1**

BZ分類 **BZ1**

器具効率	90 %	天井	80 %				70 %				50 %				30 %				0 %	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	90 %		壁	10 %				10 %				10 %				10 %				0 %
		床	10 %				10 %				10 %				10 %				0 %	
		室指数	照明率 (X0.01)																ZCM	
保守率	良 0.67	0.6	77	71	68	66	76	71	68	66	75	70	68	65	74	70	67	65	64	
	中 0.63	0.8	82	77	74	72	81	77	74	71	80	76	73	71	78	75	73	71	70	
	否 0.56	1.0	85	81	78	75	84	80	77	75	83	79	77	75	81	78	76	75	73	
下方投影面積	cm ²	1.25	87	84	81	79	87	83	81	79	85	82	80	78	84	81	79	78	76	
		1.5	89	86	83	81	88	85	83	81	87	84	82	80	85	83	81	80	78	
等価発光面積	cm ²	2.0	91	89	86	85	90	88	86	84	89	87	85	83	87	85	84	83	81	
		2.5	93	90	88	87	92	90	88	86	90	88	87	85	88	87	86	85	83	
取付高さ	器具間隔最大限		3.0	93	92	90	88	92	91	89	88	91	89	88	87	89	88	87	86	84
Hm	横方向 (A)	縦方向 (B)	4.0	95	93	92	90	94	92	91	90	92	91	90	89	90	89	88	87	85
	0.41Hm	0.41Hm	5.0	95	94	93	92	94	93	92	91	92	91	91	90	90	90	89	88	86
			7.0	96	95	94	93	95	94	93	93	93	92	92	91	91	91	90	87	
			10.0	96	96	95	95	95	95	94	94	93	93	92	92	92	91	91	90	88

