

屋内照明器具特性	
品番 (品名)	L G D 1 1 0 9 L
光源	LED2700_70_335 ×1 335.0 l m
管理番号	K0185758 (0) D 1
B Z 分類	B Z 2

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	100 %	室指数	照明率 (X0.01)																			Z C M	
下方光束																									
保守率		良 中 否	0.67	0.6	67	57	51	46	66	57	51	46	64	56	50	46	62	55	50	46	44				
			0.63	0.8	77	68	62	58	76	68	62	58	74	67	62	58	72	66	61	57	56				
			1.0	84	76	70	66	82	75	70	66	80	74	69	65	78	73	68	65	63					
			0.56	1.25	89	82	77	73	87	81	76	73	85	80	76	72	83	78	75	72	70				
下方投影面積		c m ²	1.5	92	86	81	78	91	85	81	77	88	84	80	77	86	82	79	76	74					
等価発光面積			c m ²	2.0	96	91	88	84	95	91	87	84	93	89	86	83	90	87	85	82	80				
				2.5	99	95	91	89	98	94	91	88	95	92	89	87	93	90	88	86	84				
取付 高さ	器具間隔最大限			2.5	99	95	91	89	98	94	91	88	95	92	89	87	93	90	88	86	84				
	横方向 (A)		縦方向 (B)	3.0	100	97	94	91	99	96	93	91	97	94	92	90	95	92	90	89	86				
H m	1.11 H m	1.11 H m	4.0	102	100	97	95	101	99	97	95	99	97	95	93	97	95	93	92	90					
			5.0	104	101	100	98	102	100	99	97	100	98	97	95	98	97	95	94	92					
			7.0	105	103	101	100	104	102	101	100	101	100	99	98	99	98	97	96	94					
			10.0	106	105	104	103	105	104	103	102	103	102	101	100	100	100	99	98	96					

