

屋内照明器具特性	
品番 (品名)	L G D 9 1 0 7
光源	L L D 2 0 0 0 L C T 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 8 7 6 6 4 (2) D R 1
B Z 分類	B Z 2 / 1 . 8 / B Z 3

器具効率		66 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 6 7	0 . 6	4 4	3 7	3 3	3 0	4 3	3 7	3 3	3 0	4 2	3 6	3 3	3 0	4 1	3 6	3 2	3 0	2 9
			0 . 6 3	0 . 8	5 0	4 4	4 0	3 7	4 9	4 4	4 0	3 7	4 8	4 3	3 9	3 7	4 6	4 2	3 9	3 7	3 5
			0 . 5 6	1 . 0	5 4	4 9	4 5	4 2	5 3	4 8	4 4	4 2	5 2	4 7	4 4	4 1	5 0	4 6	4 3	4 1	4 0
				1 . 2 5	5 7	5 2	4 9	4 6	5 6	5 2	4 9	4 6	5 5	5 1	4 8	4 6	5 3	5 0	4 7	4 5	4 4
下方投影面積		c m ²	1 . 5	5 9	5 5	5 2	4 9	5 9	5 5	5 1	4 9	5 7	5 3	5 1	4 8	5 5	5 2	5 0	4 8	4 7	
			等価発光面積	c m ²	2 . 0	6 2	5 9	5 6	5 3	6 1	5 8	5 5	5 3	6 0	5 7	5 5	5 3	5 8	5 6	5 4	5 2
取付 高さ	器具間隔最大限		2 . 5	6 4	6 1	5 9	5 6	6 3	6 0	5 8	5 6	6 2	5 9	5 7	5 5	6 0	5 8	5 6	5 5	5 3	
	横方向 (A) 縦方向 (B)		3 . 0	6 5	6 3	6 0	5 8	6 4	6 2	6 0	5 8	6 3	6 1	5 9	5 7	6 1	5 9	5 8	5 7	5 5	
H m	1 . 1 7 H m	1 . 1 7 H m	4 . 0	6 7	6 5	6 3	6 1	6 6	6 4	6 2	6 1	6 4	6 3	6 1	6 0	6 3	6 1	6 0	5 9	5 7	
			5 . 0	6 8	6 6	6 4	6 3	6 7	6 5	6 4	6 3	6 5	6 4	6 3	6 2	6 4	6 3	6 2	6 1	5 9	
			7 . 0	6 9	6 7	6 6	6 5	6 8	6 7	6 6	6 5	6 6	6 5	6 4	6 4	6 5	6 4	6 3	6 3	6 1	
			1 0 . 0	6 9	6 9	6 8	6 7	6 9	6 8	6 7	6 6	6 7	6 6	6 6	6 5	6 6	6 5	6 5	6 4	6 2	

