

屋内照明器具特性	
品番 (品名)	L G D 9 1 0 8
光源	L L D 3 0 2 0 L C T 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 8 7 6 7 0 (1) D R 1
B Z 分類	B Z 1

器具効率		6 8 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		6 8 %	室指数	照明率 (X 0 . 0 1)																		Z C M	
下方光束																							
保守率		良 中 否	0 . 6	5 9	5 6	5 3	5 2	5 9	5 5	5 3	5 2	5 8	5 5	5 3	5 2	5 7	5 5	5 3	5 1	5 1			
			0 . 8	6 3	6 0	5 7	5 6	6 2	5 9	5 7	5 6	6 1	5 9	5 7	5 6	6 0	5 8	5 7	5 5	5 5			
			1 . 0	6 5	6 2	6 0	5 9	6 4	6 2	6 0	5 8	6 3	6 1	5 9	5 8	6 2	6 1	5 9	5 8	5 7			
			0 . 5 6	1 . 2 5	6 7	6 4	6 2	6 1	6 6	6 4	6 2	6 1	6 5	6 3	6 2	6 0	6 4	6 2	6 1	6 0	5 9		
下方投影面積		c m ²	1 . 5	6 8	6 6	6 4	6 3	6 7	6 5	6 4	6 2	6 6	6 4	6 3	6 2	6 5	6 4	6 2	6 1	6 0			
等価発光面積			c m ²	2 . 0	6 9	6 7	6 6	6 5	6 9	6 7	6 6	6 4	6 7	6 6	6 5	6 4	6 6	6 5	6 4	6 3	6 2		
取付 高さ	器具間隔最大限		2 . 5	7 0	6 9	6 7	6 6	6 9	6 8	6 7	6 6	6 8	6 7	6 6	6 5	6 7	6 6	6 5	6 4	6 3			
	横方向 (A)		縦方向 (B)	3 . 0	7 1	6 9	6 8	6 7	7 0	6 9	6 8	6 7	6 9	6 8	6 7	6 6	6 7	6 7	6 6	6 5	6 4		
H m	0 . 4 3 H m		0 . 4 3 H m	4 . 0	7 1	7 0	6 9	6 9	7 1	7 0	6 9	6 8	6 9	6 8	6 8	6 7	6 8	6 7	6 7	6 6	6 5		
				5 . 0	7 2	7 1	7 0	6 9	7 1	7 0	7 0	6 9	7 0	6 9	6 8	6 8	6 8	6 8	6 7	6 7	6 5		
				7 . 0	7 2	7 2	7 1	7 1	7 1	7 1	7 0	7 0	7 0	7 0	6 9	6 9	6 9	6 8	6 8	6 8	6 6		
				1 0 . 0	7 3	7 2	7 2	7 1	7 2	7 1	7 1	7 1	7 0	7 0	7 0	6 9	6 9	6 9	6 8	6 8	6 6		

