

屋内照明器具特性	
品番 (品名)	L G D 9 1 0 8
光源	L L D 4 0 0 0 1 C Q 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 9 1 2 6 6 (1) D R 1
B Z 分類	B Z 1

器具効率		4 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		4 0 %																				
保守率		良 中 否	0 . 6 7	0 . 6	3 0	2 7	2 5	2 3	3 0	2 7	2 5	2 3	2 9	2 6	2 5	2 3	2 8	2 6	2 4	2 3	2 3	
			0 . 6 3	0 . 8	3 4	3 1	2 9	2 8	3 3	3 1	2 9	2 7	3 2	3 0	2 9	2 7	3 2	3 0	2 8	2 7	2 7	
			0 . 5 6	1 . 0	3 6	3 3	3 2	3 0	3 5	3 3	3 1	3 0	3 5	3 3	3 1	3 0	3 4	3 2	3 1	3 0	2 9	
				1 . 2 5	3 7	3 5	3 4	3 2	3 7	3 5	3 3	3 2	3 6	3 4	3 3	3 2	3 5	3 4	3 3	3 2	3 1	
下方投影面積		c m ²	1 . 5	3 8	3 6	3 5	3 4	3 8	3 6	3 5	3 4	3 7	3 6	3 4	3 3	3 6	3 5	3 4	3 3	3 3		
等価発光面積		c m ²	2 . 0	4 0	3 8	3 7	3 6	3 9	3 8	3 7	3 6	3 8	3 7	3 6	3 5	3 8	3 7	3 6	3 5	3 4		
取付 高さ	器具間隔最大限		2 . 5	4 0	3 9	3 8	3 7	4 0	3 9	3 8	3 7	3 9	3 8	3 7	3 7	3 8	3 8	3 7	3 6	3 5		
	横方向 (A) 縦方向 (B)		3 . 0	4 1	4 0	3 9	3 8	4 0	3 9	3 9	3 8	4 0	3 9	3 8	3 7	3 9	3 8	3 8	3 7	3 6		
H m	1 . 0 3 H m	1 . 0 3 H m	4 . 0	4 2	4 1	4 0	3 9	4 1	4 0	4 0	3 9	4 0	4 0	3 9	3 8	3 9	3 9	3 8	3 8	3 7		
			5 . 0	4 2	4 1	4 1	4 0	4 1	4 1	4 0	4 0	4 1	4 0	4 0	3 9	4 0	3 9	3 9	3 9	3 8		
			7 . 0	4 2	4 2	4 1	4 1	4 2	4 1	4 1	4 1	4 1	4 1	4 0	4 0	4 0	4 0	4 0	3 9	3 8		
			1 0 . 0	4 3	4 2	4 2	4 2	4 2	4 2	4 2	4 1	4 1	4 1	4 1	4 1	4 0	4 0	4 0	4 0	3 9		

