

屋内照明器具特性	
品番 (品名)	L G D 9 1 0 8
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 l m
管理番号	K0191278 (1) DR 1
B Z 分類	B Z 1

器具効率		35 %	反射率	天井	80 %					70 %					50 %					30 %					0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %						
				床	10 %					10 %					10 %					10 %					0 %		
上方光束		0 %	室指数	照明率 (X0.01)																			Z C M				
下方光束		35 %																									
保守率		良 中 否	0.67	0.6	27	24	22	21	26	24	22	21	26	24	22	21	25	23	22	21	21						
			0.63	0.8	30	27	26	25	29	27	26	24	29	27	25	24	28	26	25	24	24						
			0.56	1.0	31	29	28	27	31	29	28	27	30	29	27	26	30	28	27	26	26						
				1.25	33	31	30	29	32	31	29	28	32	30	29	28	31	30	29	28	28						
下方投影面積		c m ²	1.5	33	32	31	30	33	32	31	30	32	31	30	29	32	31	30	29	29							
等価発光面積			c m ²	2.0	34	33	32	31	34	33	32	31	33	32	32	31	33	32	31	30							
取付 高さ	器具間隔最大限			2.5	35	34	33	32	35	34	33	32	34	33	33	32	33	33	32	31							
	横方向 (A)		縦方向 (B)	3.0	36	35	34	33	35	34	34	33	34	34	33	33	34	33	33	32							
H m	0.95 H m		0.95 H m	4.0	36	35	35	34	36	35	34	34	35	34	34	33	34	34	33	32							
				5.0	36	36	35	35	36	35	35	35	35	35	34	34	34	34	34	33							
				7.0	37	36	36	36	36	36	36	35	36	35	35	35	35	35	34	33							
				10.0	37	37	36	36	37	36	36	36	36	36	35	35	35	35	35	34							

