

屋内照明器具特性	
品番 (品名)	LGS9005
光源	LLD4000LCT1 ×1 845.0 lm
管理番号	K0190540 (1) DR1
BZ分類	BZ2/0.9/BZ3

器具効率		58 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
				室指数	照明率 (X0.01)																Z	CM	
保守率		良 中 否	0.67	0.6	38	33	29	26	38	32	29	26	37	32	29	26	36	31	28	26	25		
			0.63	0.8	44	38	35	32	43	38	35	32	42	37	34	32	40	37	34	32	31		
			0.56	1.0	47	42	39	36	46	42	38	36	45	41	38	36	44	40	38	36	35		
				1.25	50	46	42	40	49	45	42	40	48	44	42	39	46	43	41	39	38		
下方投影面積 等価発光面積		cm ²		1.5	52	48	45	43	51	47	45	42	50	47	44	42	48	46	43	42	40		
				2.0	54	51	49	46	54	51	48	46	52	50	48	46	51	49	47	45	44		
				2.5	56	53	51	49	55	53	51	49	54	52	50	48	52	51	49	48	46		
				3.0	57	55	53	51	56	54	52	51	55	53	51	50	53	52	51	49	48		
H	m	1.14 H	m	1.14 H	m	4.0	58	57	55	53	58	56	54	53	56	55	54	52	55	54	53	52	50
						5.0	59	58	56	55	59	57	56	55	57	56	55	54	56	55	54	53	51
						7.0	60	59	58	57	60	58	57	57	58	57	56	56	57	56	55	55	53
						10.0	61	60	59	59	60	59	59	58	59	58	58	57	58	57	57	56	54

