

屋内照明器具特性	
品番 (品名)	L G S 9 0 0 5
光源	LLD2000LCT1 ×1 531.0 lm
管理番号	K0190538 (1) DR 1
B Z 分類	BZ2 / 1.1 / BZ3

器具効率		61 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.67	0.6	41	35	31	28	40	34	31	28	39	34	30	28	38	33	30	28	27				
			0.63	0.8	46	41	37	34	46	40	37	34	44	40	36	34	43	39	36	34	33				
			0.56	1.0	50	45	41	38	49	44	41	38	48	43	40	38	46	43	40	38	37				
				1.25	53	48	45	42	52	48	45	42	50	47	44	42	49	46	43	41	40				
下方投影面積		cm ²		1.5	55	51	48	45	54	50	47	45	52	49	47	44	51	48	46	44	43				
				2.0	58	54	51	49	57	54	51	49	55	52	50	48	54	51	50	48	47				
等価発光面積		cm ²		2.5	59	56	54	52	58	56	53	52	57	55	53	51	55	53	52	50	49				
				3.0	60	58	56	54	60	57	55	53	58	56	54	53	56	55	53	52	51				
H _m	1.17 H _m	1.17 H _m		4.0	62	60	58	57	61	59	58	56	59	58	57	55	58	57	56	54	53				
				5.0	63	61	60	58	62	60	59	58	60	59	58	57	59	58	57	56	54				
				7.0	64	62	61	60	63	62	61	60	61	60	60	59	60	59	58	58	56				
				10.0	64	64	63	62	64	63	62	61	62	62	61	60	61	60	60	59	57				

