

屋内照明器具特性	
品番 (品名)	L G S 9 5 0 5
光源	L L D 2 0 0 0 C U 1 × 1 5 6 6 . 0 l m
管理番号	K 0 1 9 1 3 0 0 (1) D R 1
B Z 分類	B Z 3

器具効率		6 8 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 6 7	0 . 6	4 4	3 7	3 3	3 0	4 3	3 7	3 3	3 0	4 2	3 6	3 2	2 9	4 1	3 6	3 2	2 9	2 8
			0 . 6 3	0 . 8	5 1	4 4	4 0	3 7	5 0	4 4	4 0	3 7	4 8	4 3	3 9	3 6	4 7	4 2	3 9	3 6	3 5
			0 . 5 6	1 . 0	5 5	4 9	4 5	4 2	5 4	4 8	4 4	4 1	5 2	4 8	4 4	4 1	5 1	4 7	4 3	4 1	4 0
				1 . 2 5	5 8	5 3	4 9	4 6	5 7	5 3	4 9	4 6	5 6	5 1	4 8	4 6	5 4	5 0	4 8	4 5	4 4
下方投影面積		c m ²		1 . 5	6 1	5 6	5 2	4 9	6 0	5 5	5 2	4 9	5 8	5 4	5 1	4 9	5 6	5 3	5 1	4 8	4 7
			等価発光面積	c m ²	2 . 0	6 4	6 0	5 7	5 4	6 3	5 9	5 6	5 4	6 1	5 8	5 5	5 3	5 9	5 7	5 5	5 3
取付 高さ	器具間隔最大限			2 . 5	6 6	6 2	6 0	5 7	6 5	6 2	5 9	5 7	6 3	6 0	5 8	5 6	6 1	5 9	5 7	5 6	5 4
	横方向 (A)		縦方向 (B)	3 . 0	6 7	6 4	6 2	6 0	6 6	6 3	6 1	5 9	6 4	6 2	6 0	5 8	6 3	6 1	5 9	5 8	5 6
H m	1 . 1 6 H m		1 . 1 6 H m	4 . 0	6 9	6 6	6 4	6 3	6 8	6 6	6 4	6 2	6 6	6 4	6 3	6 1	6 4	6 3	6 2	6 0	5 9
				5 . 0	7 0	6 8	6 6	6 5	6 9	6 7	6 5	6 4	6 7	6 6	6 4	6 3	6 5	6 4	6 3	6 2	6 0
				7 . 0	7 1	6 9	6 8	6 7	7 0	6 9	6 7	6 6	6 8	6 7	6 6	6 5	6 7	6 6	6 5	6 4	6 2
				1 0 . 0	7 2	7 1	7 0	6 9	7 1	7 0	6 9	6 8	6 9	6 8	6 8	6 7	6 8	6 7	6 6	6 6	6 4

