

屋内照明器具特性	
品番 (品名)	L G S 9 5 0 5
光源	LLD4000LCE1 ×1 845.0 l m
管理番号	K0191282 (1) DR 1
B Z 分類	BZ2 / 0.9 / BZ3

器具効率		58 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束		0 %		床	10 %				10 %				10 %				10 %				0 %
下方光束		58 %		室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	38	33	29	26	38	32	29	26	37	32	29	26	36	31	28	26	25
			0.63	0.8	44	38	35	32	43	38	35	32	42	37	34	32	40	37	34	32	31
				1.0	47	42	39	36	46	42	38	36	45	41	38	36	44	40	38	36	35
			0.56	1.25	50	46	42	40	49	45	42	40	48	44	42	39	46	43	41	39	38
下方投影面積		c m ²	1.5	52	48	45	43	51	47	45	42	50	47	44	42	48	46	43	42	40	
等価発光面積		c m ²	2.0	54	51	49	46	54	51	48	46	52	50	48	46	51	49	47	45	44	
取付 高さ	器具間隔最大限		2.5	56	53	51	49	55	53	51	49	54	52	50	48	52	51	49	48	46	
	横方向 (A)	縦方向 (B)	3.0	57	55	53	51	56	54	52	51	55	53	51	50	53	52	51	49	48	
H m	1.14 H m	1.14 H m	4.0	58	57	55	53	58	56	54	53	56	55	54	52	55	54	53	52	50	
			5.0	59	58	56	55	59	57	56	55	57	56	55	54	56	55	54	53	51	
			7.0	60	59	58	57	60	58	57	57	58	57	56	56	57	56	55	55	53	
			10.0	61	60	59	59	60	59	59	58	59	58	58	57	58	57	57	56	54	

