

屋内照明器具特性	
品番 (品名)	L G S 9 5 0 5
光源	L L D 2 0 0 0 M L C E 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 9 1 3 7 2 (1) D R 1
B Z 分類	B Z 3 / 0 . 7 / B Z 2 / 0 . 9 / B Z 3

器具効率		6 7 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		6 7 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 7	0 . 6	4 4	3 8	3 3	3 0	4 4	3 7	3 3	3 0	4 2	3 7	3 3	3 0	4 1	3 6	3 3	3 0	2 9	
			0 . 6 3	0 . 8	5 0	4 4	4 0	3 7	5 0	4 4	4 0	3 7	4 8	4 3	3 9	3 7	4 7	4 2	3 9	3 7	3 5	
			0 . 5 6	1 . 0	5 4	4 9	4 5	4 2	5 3	4 8	4 4	4 1	5 2	4 7	4 4	4 1	5 0	4 6	4 3	4 1	4 0	
				1 . 2 5	5 8	5 3	4 9	4 6	5 7	5 2	4 9	4 6	5 5	5 1	4 8	4 5	5 3	5 0	4 7	4 5	4 4	
下方投影面積		c m ²	1 . 5	6 0	5 5	5 2	4 9	5 9	5 5	5 1	4 9	5 7	5 4	5 1	4 8	5 6	5 3	5 0	4 8	4 7		
等価発光面積		c m ²	2 . 0	6 3	5 9	5 6	5 4	6 2	5 8	5 6	5 3	6 0	5 7	5 5	5 3	5 9	5 6	5 4	5 2	5 1		
取付 高さ	器具間隔最大限		2 . 5	6 5	6 2	5 9	5 7	6 4	6 1	5 8	5 6	6 2	6 0	5 7	5 6	6 0	5 8	5 7	5 5	5 3		
	横方向 (A) 縦方向 (B)		3 . 0	6 6	6 3	6 1	5 9	6 5	6 2	6 0	5 8	6 3	6 1	5 9	5 8	6 2	6 0	5 8	5 7	5 5		
H m	1 . 1 3 H m	1 . 1 3 H m	4 . 0	6 8	6 5	6 3	6 2	6 7	6 5	6 3	6 1	6 5	6 3	6 2	6 0	6 3	6 2	6 1	5 9	5 8		
			5 . 0	6 8	6 7	6 5	6 4	6 8	6 6	6 4	6 3	6 6	6 5	6 3	6 2	6 4	6 3	6 2	6 1	5 9		
			7 . 0	7 0	6 8	6 7	6 6	6 9	6 7	6 6	6 5	6 7	6 6	6 5	6 4	6 6	6 5	6 4	6 3	6 1		
			1 0 . 0	7 0	6 9	6 9	6 8	7 0	6 9	6 8	6 7	6 8	6 7	6 6	6 6	6 6	6 6	6 5	6 5	6 3		

