

屋内照明器具特性	
品番 (品名)	LGS9505
光源	LLD40402CQ1 (SHUKOU) ×1 620.0 l m
管理番号	K0191366 (1) DR 1
BZ分類	BZ1

器具効率		86 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		86 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束																								
保守率		良	0.67	0.6	76	72	69	68	76	72	69	67	75	71	69	67	74	71	69	67	66			
		中	0.63	0.8	80	76	74	72	79	76	73	72	78	75	73	71	77	75	73	71	70			
		否	0.56	1.0	82	79	76	75	82	79	76	74	80	78	76	74	79	77	75	74	73			
				1.25	84	81	79	77	84	81	79	77	82	80	78	77	81	79	77	76	75			
下方投影面積		c m ²	1.5	86	83	81	79	85	82	80	79	83	81	80	78	82	80	79	78	76				
等価発光面積			c m ²	2.0	87	85	83	82	86	84	83	81	85	83	82	81	83	82	81	80	78			
取付高さ	器具間隔最大限		2.5	88	86	85	83	87	86	84	83	86	84	83	82	84	83	82	81	80				
	横方向 (A)		縦方向 (B)	3.0	89	87	86	85	88	87	85	84	86	85	84	83	85	84	83	82	80			
H m	0.76 H m	0.76 H m	4.0	90	89	87	86	89	88	87	86	87	86	85	85	86	85	84	83	82				
			5.0	90	89	88	88	90	89	88	87	88	87	86	86	86	85	85	84	82				
			7.0	91	90	90	89	90	89	89	88	88	88	87	87	87	86	86	85	83				
			10.0	92	91	90	90	91	90	90	89	89	88	88	88	87	87	86	86	84				

