

屋内照明器具特性	
品番 (品名)	L G S 9 5 0 5
光源	LLD2000LCS1 ×1 580.0 lm
管理番号	K0191291 (1) DR 1
B Z 分類	BZ3

器具効率		57 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) Z CM															
保守率		良 中 否	0.67	0.6	37	31	27	25	36	31	27	25	35	30	27	25	34	30	27	25	24	
			0.63	0.8	42	37	33	31	42	37	33	31	40	36	33	30	39	35	32	30	29	
			0.56	1.0	46	41	37	35	45	40	37	35	44	40	37	34	42	39	36	34	33	
				1.25	49	44	41	38	48	44	41	38	46	43	40	38	45	42	40	38	37	
下方投影面積		cm ²	1.5	51	47	44	41	50	46	43	41	48	45	43	41	47	44	42	40	39		
			等価発光面積	cm ²	2.0	53	50	47	45	52	49	47	45	51	48	46	44	50	47	46	44	43
取付 高さ	器具間隔最大限		2.5	55	52	50	48	54	52	49	48	53	50	49	47	51	49	48	46	45		
	横方向 (A) 縦方向 (B)		3.0	56	54	51	50	55	53	51	49	54	52	50	49	52	51	49	48	47		
H m	1.08 H m	1.08 H m	4.0	57	55	54	52	57	55	53	52	55	54	52	51	54	53	51	50	49		
			5.0	58	57	55	54	57	56	55	53	56	55	54	53	55	54	53	52	50		
			7.0	59	58	57	56	58	57	56	55	57	56	55	54	56	55	54	54	52		
			10.0	60	59	58	57	59	58	58	57	58	57	56	56	56	56	55	55	53		

