

屋内照明器具特性	
品番 (品名)	LGS9506
光源	LLD3020CU1 ×1 615.0 lm
管理番号	K0191303 (1) DR1
BZ分類	BZ1

器具効率		77 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		77 %																						
保守率		良	0.67	0.6	69	65	63	62	69	65	63	61	68	65	63	61	67	64	63	61	61			
		中	0.63	0.8	73	70	67	66	72	69	67	66	71	69	67	65	70	68	67	65	64			
		否	0.56	1.0	75	72	70	68	74	72	70	68	73	71	69	68	72	70	69	68	67			
				1.25	77	74	72	71	76	74	72	71	75	73	72	70	74	72	71	70	69			
下方投影面積		c m ²	1.5	78	76	74	73	77	75	74	72	76	74	73	72	75	73	72	71	70				
等価発光面積			c m ²	2.0	79	78	76	75	79	77	76	75	77	76	75	74	76	75	74	73	72			
取付	器具間隔最大限		2.5	80	79	78	76	80	78	77	76	78	77	76	75	77	76	75	74	73				
高さ	横方向 (A)		縦方向 (B)	3.0	81	80	78	78	80	79	78	77	79	78	77	76	77	77	76	75	74			
H m	0.34 H m			0.34 H m	4.0	82	81	80	79	81	80	79	78	79	79	78	77	78	77	77	76	75		
			5.0	82	81	81	80	81	81	80	79	80	79	79	78	78	78	77	77	75				
			7.0	83	82	81	81	82	81	81	80	80	80	79	79	79	78	78	78	76				
			10.0	83	83	82	82	82	82	81	81	80	80	80	80	79	79	79	78	76				

