

屋内照明器具特性	
品番 (品名)	LGS9506
光源	LLD3020MLCB1 ×1 715.0 lm
管理番号	K0191375 (1) DR1
BZ分類	BZ1

器具効率		76 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		76 %	室指数	照明率 (X0.01)																		Z C M
下方光束																						
保守率		良 中 否	0.6	66	63	60	58	66	62	60	58	65	62	60	58	64	62	60	58	58		
			0.8	70	67	65	63	70	67	65	63	69	66	64	63	68	66	64	63	62		
			1.0	73	70	68	66	72	69	67	66	71	69	67	65	70	68	66	65	64		
			0.56	1.25	75	72	70	68	74	72	70	68	73	71	69	68	72	70	69	67	67	
下方投影面積		c m ²	1.5	76	73	72	70	75	73	71	70	74	72	71	69	73	71	70	69	68		
等価発光面積			c m ²	2.0	77	75	74	73	77	75	73	72	75	74	73	72	74	73	72	71	70	
取付 高さ	器具間隔最大限		2.5	78	77	75	74	77	76	75	74	76	75	74	73	75	74	73	72	71		
	横方向 (A)		縦方向 (B)	3.0	79	77	76	75	78	77	76	75	77	76	75	74	75	74	74	73	72	
H m	0.43 H m	0.43 H m	4.0	80	79	78	77	79	78	77	76	77	77	76	75	76	75	75	74	73		
			5.0	80	79	78	78	79	78	78	77	78	77	77	76	76	76	75	75	73		
			7.0	81	80	79	79	80	79	79	78	78	78	77	77	77	76	76	76	74		
			10.0	81	81	80	80	80	80	79	79	78	78	78	78	77	77	77	76	74		

