

屋内照明器具特性	
品番 (品名)	L G S 9 5 0 6
光源	L L D 2 0 0 0 1 C Q 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 9 1 2 9 7 (1) D R 1
B Z 分類	B Z 1

器具効率		3 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	2 6	2 4	2 2	2 1	2 6	2 4	2 2	2 1	2 5	2 3	2 2	2 1	2 5	2 3	2 2	2 1	2 0
			0 . 6 3	0 . 8	2 9	2 7	2 5	2 4	2 9	2 6	2 5	2 4	2 8	2 6	2 5	2 4	2 7	2 6	2 5	2 4	2 3
			0 . 5 6	1 . 0	3 0	2 9	2 7	2 6	3 0	2 8	2 7	2 6	3 0	2 8	2 7	2 6	2 9	2 8	2 7	2 6	2 5
				1 . 2 5	3 2	3 0	2 9	2 8	3 1	3 0	2 9	2 8	3 1	2 9	2 8	2 8	3 0	2 9	2 8	2 7	2 7
下方投影面積 等価発光面積		c m ² c m ²		1 . 5	3 3	3 1	3 0	2 9	3 2	3 1	3 0	2 9	3 2	3 0	2 9	2 9	3 1	3 0	2 9	2 8	2 8
				2 . 0	3 4	3 2	3 1	3 1	3 3	3 2	3 1	3 0	3 3	3 2	3 1	3 0	3 2	3 1	3 0	3 0	2 9
				2 . 5	3 4	3 3	3 2	3 2	3 4	3 3	3 2	3 1	3 3	3 2	3 2	3 1	3 2	3 2	3 1	3 1	3 0
取付 高さ	器具間隔最大限			3 . 0	3 5	3 4	3 3	3 2	3 4	3 3	3 3	3 2	3 3	3 3	3 2	3 2	3 3	3 2	3 2	3 1	3 1
	横方向 (A)	縦方向 (B)		4 . 0	3 5	3 4	3 4	3 3	3 5	3 4	3 4	3 3	3 4	3 3	3 3	3 3	3 3	3 3	3 2	3 2	3 1
H m	0 . 9 8 H m	0 . 9 8 H m		5 . 0	3 5	3 5	3 4	3 4	3 5	3 4	3 4	3 4	3 4	3 4	3 3	3 3	3 4	3 3	3 3	3 3	3 2
				7 . 0	3 6	3 5	3 5	3 5	3 5	3 5	3 5	3 4	3 5	3 4	3 4	3 4	3 4	3 4	3 3	3 3	3 2
				1 0 . 0	3 6	3 6	3 5	3 5	3 6	3 5	3 5	3 5	3 5	3 5	3 4	3 4	3 4	3 4	3 4	3 4	3 3

