

屋内照明器具特性	
品番 (品名)	XAD3108V
光源	LLD4000VCE1 ×1 845.0 lm
管理番号	K0187668 (1) DR1
BZ分類	BZ2/1.8/BZ3

器具効率		66 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z
保守率		良 中 否	0.67	0.6	44	37	33	30	43	37	33	30	42	36	33	30	41	36	32	30	29
			0.63	0.8	50	44	40	37	49	44	40	37	48	43	39	37	47	42	39	37	35
			0.56	1.0	54	49	45	42	53	48	44	42	52	47	44	41	50	46	44	41	40
				1.25	57	53	49	46	57	52	49	46	55	51	48	46	53	50	47	45	44
下方投影面積		cm ²		1.5	60	55	52	49	59	55	52	49	57	54	51	49	56	53	50	48	47
				2.0	63	59	56	54	62	58	56	53	60	57	55	53	58	56	54	52	51
取付 高さ	器具間隔最大限			2.5	64	61	59	57	63	61	58	56	62	59	57	56	60	58	56	55	53
	横方向 (A)		縦方向 (B)	3.0	66	63	61	59	65	62	60	58	63	61	59	58	61	60	58	57	55
H m	1.14 H m	1.14 H m		4.0	67	65	63	62	66	64	63	61	65	63	62	60	63	62	60	59	58
				5.0	68	66	65	63	67	66	64	63	66	64	63	62	64	63	62	61	59
				7.0	69	68	67	66	68	67	66	65	67	66	65	64	65	64	64	63	61
				10.0	70	69	68	67	69	68	67	67	67	67	66	65	66	65	65	64	62

