

屋内照明器具特性	
品番 (品名)	XAS5021V
光源	LLD5020VCC1 ×1 1085.0 l m
管理番号	K0187901 (0) DR 1
B Z 分類	BZ1

器具効率		78 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																			
下方光束		78 %		Z C M																			
保守率		良 中 否	0.67	0.6	64	59	56	54	64	59	56	54	63	58	56	53	62	58	55	53	53		
			0.63	0.8	69	65	62	60	69	64	62	59	67	64	61	59	66	63	61	59	58		
			0.56	1.0	72	68	66	63	72	68	65	63	70	67	65	63	69	66	64	63	62		
				1.25	75	71	69	67	74	71	68	67	73	70	68	66	71	69	67	66	65		
下方投影面積		c m ²		1.5	77	74	71	69	76	73	71	69	74	72	70	68	73	71	69	68	67		
等価発光面積			c m ²	2.0	79	76	74	72	78	76	74	72	76	74	73	71	75	73	72	71	69		
取付 高さ	器具間隔最大限		2.5	80	78	76	75	79	77	76	74	78	76	75	73	76	75	74	73	71			
	横方向 (A)		縦方向 (B)	3.0	81	79	77	76	80	78	77	76	78	77	76	75	77	76	75	74	72		
H m	0.44 H m	0.44 H m	4.0	82	80	79	78	81	80	78	77	79	78	77	76	78	77	76	75	74			
			5.0	82	81	80	79	82	80	80	79	80	79	78	77	78	78	77	76	74			
			7.0	83	82	81	81	82	81	81	80	81	80	79	79	79	78	78	77	75			
			10.0	84	83	82	82	83	82	82	81	81	81	80	80	79	79	79	78	76			

