

屋内照明器具特性	
品番 (品名)	XAS5500V
光源	LLD5000VCC1 ×1 1140.0 lm
管理番号	K0187895 (0) DR 1
BZ分類	BZ2

器具効率		89 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.67	0.6	60	51	45	42	59	51	45	42	57	50	45	41	56	49	45	41	40
			0.63	0.8	69	61	56	52	68	61	56	52	66	60	55	52	64	59	55	51	50
			0.56	1.0	75	68	63	59	74	67	62	59	72	66	62	58	70	65	61	58	57
				1.25	79	73	69	65	78	72	68	65	76	71	67	64	74	70	67	64	62
下方投影面積 等価発光面積		cm ²		1.5	82	77	72	69	81	76	72	69	79	75	71	68	77	73	70	68	66
				2.0	86	81	78	75	85	81	77	74	82	79	76	74	80	78	75	73	71
				2.5	88	84	81	79	87	84	81	78	85	82	79	77	83	80	78	76	74
				3.0	90	86	84	81	88	85	83	81	86	84	82	80	84	82	80	79	77
H m	1.25 H m	1.25 H m	4.0	91	89	87	85	90	88	86	84	88	86	84	83	86	85	83	82	80	
			5.0	93	90	89	87	91	90	88	86	89	88	86	85	87	86	85	84	81	
			7.0	94	92	91	90	93	91	90	89	91	89	88	87	89	88	87	86	83	
			10.0	95	94	93	92	94	93	92	91	92	91	90	89	90	89	88	88	85	

