

屋内照明器具特性	
品番 (品名)	XAS5520V
光源	LLD5020VCC1 ×1 1085.0 lm
管理番号	K0187898 (0) DR 1
BZ分類	BZ1

器具効率		9 2 %	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
					床	1 0 %				1 0 %				1 0 %				1 0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																Z C M	
下方光束		9 2 %																			
保守率		良	0 . 6 7	0 . 6	7 4	6 8	6 4	6 1	7 3	6 7	6 3	6 1	7 2	6 7	6 3	6 1	7 1	6 6	6 3	6 0	5 9
		中	0 . 6 3	0 . 8	8 0	7 4	7 1	6 8	7 9	7 4	7 0	6 8	7 8	7 3	7 0	6 7	7 6	7 2	6 9	6 7	6 6
		否	0 . 5 6	1 . 0	8 4	7 9	7 5	7 2	8 3	7 8	7 5	7 2	8 1	7 7	7 4	7 2	8 0	7 6	7 4	7 1	7 0
				1 . 2 5	8 7	8 2	7 9	7 6	8 6	8 2	7 9	7 6	8 4	8 1	7 8	7 6	8 3	8 0	7 7	7 5	7 4
下方投影面積		c m ²	1 . 5	8 9	8 5	8 2	8 0	8 8	8 4	8 2	7 9	8 6	8 3	8 1	7 9	8 5	8 2	8 0	7 8	7 7	
等価発光面積			c m ²	2 . 0	9 2	8 9	8 6	8 4	9 1	8 8	8 5	8 3	8 9	8 6	8 4	8 2	8 7	8 5	8 3	8 2	8 0
取付高さ	器具間隔最大限		2 . 5	9 3	9 1	8 8	8 6	9 2	9 0	8 8	8 6	9 0	8 8	8 6	8 5	8 9	8 7	8 5	8 4	8 2	
	横方向 (A)		縦方向 (B)	3 . 0	9 4	9 2	9 0	8 8	9 3	9 1	8 9	8 8	9 1	9 0	8 8	8 7	9 0	8 8	8 7	8 6	8 4
H m	0 . 4 5 H m	0 . 4 5 H m	4 . 0	9 6	9 4	9 2	9 1	9 5	9 3	9 1	9 0	9 3	9 1	9 0	8 9	9 1	9 0	8 9	8 8	8 6	
			5 . 0	9 7	9 5	9 4	9 2	9 6	9 4	9 3	9 2	9 3	9 2	9 1	9 0	9 2	9 1	9 0	8 9	8 7	
			7 . 0	9 7	9 6	9 5	9 4	9 6	9 5	9 4	9 4	9 4	9 4	9 3	9 2	9 2	9 2	9 1	9 0	8 8	
			1 0 . 0	9 8	9 7	9 7	9 6	9 7	9 6	9 6	9 5	9 5	9 4	9 4	9 3	9 3	9 3	9 2	9 2	8 9	

