

屋内照明器具特性

品番 (品名)	L G W J 5 6 9 3 5 A F														
光源	LDA5 L - D - G - E17 / S / Z4 ×1 440.0 l m														
管理番号	K0138524 (1) DR 1														
B Z 分類	BZ10														

器具効率	87 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	52 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	35 %		床	10 %				10 %				10 %				10 %				0 %
室指数			照明率 (X0.01) Z C M																	
保守率	良	0.63	0.6	37	26	19	14	33	23	17	13	26	18	13	10	19	14	10	7	2
	中	0.6	0.8	44	33	26	20	39	30	23	18	31	23	18	14	23	18	14	10	4
	否	0.56	1.0	49	39	31	25	44	35	28	23	34	28	22	18	26	21	17	14	6
			1.25	54	44	37	31	48	40	33	28	38	32	26	22	29	24	20	17	8
下方投影面積		cm ²	1.5	57	48	41	35	52	44	37	32	41	35	30	26	31	26	23	20	10
等価発光面積		cm ²	2.0	62	54	48	42	56	49	43	39	45	40	35	31	34	30	27	24	13
取付高さ	器具間隔最大限		2.5	65	58	53	47	59	53	48	43	48	43	39	35	37	33	30	27	15
	横方向 (A)	縦方向 (B)	3.0	68	61	56	51	61	56	51	47	50	45	42	38	38	35	32	30	17
H m	0.00 H m	0.00 H m	4.0	71	66	61	57	64	60	56	52	52	49	46	43	41	38	36	33	20
			5.0	73	68	64	61	66	62	59	56	54	51	48	46	42	40	38	36	21
			7.0	75	72	68	65	69	66	63	60	56	54	52	49	44	43	41	39	24
			10.0	77	74	72	70	71	68	66	64	58	56	54	53	46	45	43	42	26

