

屋内照明器具特性

品番 (品名)	LGC45810														
光源	LED6500_70_4850 x1 4850.0 lm														
管理番号	K0138131(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	11%																			
下方光束	89%																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 0.63 中 0.6 否 0.56	0.6	5.4	4.2	3.4	2.9	5.2	4.1	3.4	2.8	4.9	3.9	3.2	2.8	4.6	3.7	3.1	2.7	2.4	
		0.8	6.4	5.2	4.4	3.8	6.2	5.1	4.3	3.8	5.8	4.8	4.2	3.7	5.4	4.6	4.0	3.6	3.3	
		1.0	7.0	5.9	5.1	4.6	6.8	5.8	5.0	4.5	6.3	5.5	4.9	4.4	5.9	5.2	4.7	4.2	3.9	
		1.25	7.6	6.6	5.9	5.3	7.4	6.4	5.7	5.2	6.9	6.1	5.5	5.0	6.4	5.8	5.3	4.9	4.5	
下方投影面積	c m ²	1.5	8.0	7.1	6.4	5.8	7.8	6.9	6.2	5.7	7.3	6.6	6.0	5.5	6.8	6.2	5.7	5.3	4.9	
		2.0	8.6	7.8	7.1	6.6	8.3	7.6	7.0	6.5	7.8	7.2	6.7	6.3	7.3	6.8	6.4	6.1	5.6	
		2.5	8.9	8.2	7.7	7.2	8.7	8.0	7.5	7.1	8.1	7.6	7.2	6.8	7.7	7.2	6.9	6.5	6.1	
取付高さ	器具間隔最大限																			
	横方向 (A)	縦方向 (B)																		
1.5m	1.96m	1.96m	4.0	9.5	9.0	8.6	8.2	9.2	8.8	8.4	8.0	8.7	8.4	8.0	7.7	8.2	7.9	7.7	7.4	6.9
2	2.57	2.58	5.0	9.7	9.3	8.9	8.6	9.4	9.1	8.7	8.4	8.9	8.6	8.3	8.1	8.4	8.2	8.0	7.7	7.2
2.5	3.19	3.2	7.0	9.9	9.6	9.3	9.1	9.7	9.4	9.1	8.9	9.2	8.9	8.7	8.5	8.7	8.5	8.3	8.2	7.6
3	3.76	3.77	10.0	10.1	9.9	9.7	9.5	9.8	9.6	9.4	9.3	9.4	9.2	9.0	8.9	8.9	8.8	8.6	8.5	7.9

