

屋内照明器具特性	
品番 (品名)	LGC65807
光源	LED6500_70_5600 x1 5600.0 lm
管理番号	K0157522(0)DB1
BZ分類	BZ6/0.7/BZ5/3.5/BZ6/4.5/BZ5 /6.0/BZ6

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	11%	床	10%				10%				10%				10%				0%	
下方光束	89%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	53	41	33	27	51	40	32	27	48	38	31	26	44	36	30	25	22
	中	0.6	0.8	63	50	42	36	60	49	41	36	56	47	40	35	52	44	38	34	31
	否	0.56	1.0	69	57	49	43	66	56	48	43	62	53	46	41	58	50	45	40	36
			1.25	75	64	56	50	72	62	55	49	67	59	53	48	63	56	51	46	42
下方投影面積	c m ²		1.5	79	69	62	56	76	67	60	55	71	64	58	53	67	60	55	51	47
	等価発光面積		c m ²	2.0	84	76	69	64	82	74	68	63	77	70	65	60	72	67	62	58
取付高さ	器具間隔最大限		2.5	88	81	75	70	85	79	73	68	80	75	70	66	75	71	67	63	58
	横方向 (A)	縦方向 (B)	3.0	91	84	79	74	88	82	77	73	83	78	74	70	78	74	70	67	62
1.5m	1.95 m	1.95 m	4.0	94	89	84	80	91	87	82	78	86	82	79	75	81	78	75	72	67
2	2.57	2.57	5.0	96	92	88	84	93	89	86	82	88	85	82	79	84	81	78	76	70
2.5	3.13	3.13	7.0	99	95	92	89	96	93	90	87	91	88	86	84	86	84	82	80	75
3	3.76	3.76	10.0	101	98	96	93	98	96	93	91	93	91	89	88	88	87	85	84	78

