

| | |
|----------|-----------------------------|
| 屋内照明器具特性 | |
| 品番 (品名) | LGCX38201 |
| 光源 | LED6200_70_4299 x1 4299.0lm |
| 管理番号 | K0156528(0)D1 |
| BZ分類 | BZ6/1.1/BZ5/3.5/BZ6/4.5/BZ5 |

| | | | | | | | | | | | | | | | | | | | | |
|--------|-----------------|---------|-------------|------|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|----|-----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | 上方光束 26% | | 下方光束 74% | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 |
| 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | | | | ZCM |
| 保守率 | 良 | 0.63 | 0.6 | 51 | 39 | 31 | 26 | 48 | 37 | 30 | 25 | 44 | 34 | 28 | 23 | 39 | 31 | 26 | 22 | 18 |
| | 中 | 0.6 | 0.8 | 60 | 48 | 40 | 35 | 57 | 46 | 39 | 34 | 51 | 43 | 36 | 31 | 46 | 39 | 34 | 29 | 25 |
| | 否 | 0.56 | 1.0 | 67 | 55 | 47 | 41 | 63 | 53 | 46 | 40 | 57 | 49 | 42 | 38 | 51 | 44 | 39 | 35 | 30 |
| | | | 0.56 | 1.25 | 72 | 62 | 54 | 48 | 69 | 59 | 52 | 47 | 62 | 54 | 48 | 44 | 56 | 50 | 45 | 41 |
| 下方投影面積 | cm ² | | 1.5 | 76 | 67 | 60 | 54 | 73 | 64 | 57 | 52 | 66 | 59 | 53 | 49 | 59 | 54 | 49 | 45 | 39 |
| 等価発光面積 | cm ² | | 2.0 | 82 | 74 | 67 | 62 | 78 | 71 | 65 | 60 | 71 | 65 | 60 | 56 | 64 | 59 | 55 | 52 | 45 |
| 取付高さ | 器具間隔最大限 | | 2.5 | 86 | 79 | 73 | 68 | 82 | 75 | 70 | 65 | 74 | 69 | 65 | 61 | 67 | 63 | 60 | 56 | 49 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 88 | 82 | 77 | 72 | 84 | 79 | 74 | 70 | 77 | 72 | 68 | 65 | 70 | 66 | 63 | 60 | 52 |
| 1.5m | 1.94m | 2.02m | 4.0 | 91 | 86 | 82 | 78 | 87 | 83 | 79 | 75 | 80 | 76 | 73 | 70 | 73 | 70 | 67 | 65 | 56 |
| 2 | 2.56 | 2.66 | 5.0 | 94 | 89 | 86 | 82 | 89 | 86 | 82 | 79 | 82 | 79 | 76 | 73 | 75 | 72 | 70 | 68 | 59 |
| 2.5 | 3.19 | 3.32 | 7.0 | 96 | 93 | 90 | 87 | 92 | 89 | 86 | 84 | 84 | 82 | 80 | 78 | 77 | 75 | 73 | 72 | 63 |
| 3 | 3.79 | 3.94 | 10.0 | 98 | 95 | 93 | 91 | 94 | 92 | 90 | 88 | 86 | 85 | 83 | 81 | 79 | 78 | 76 | 75 | 66 |

