

屋内照明器具特性	
品番 (品名)	LGCX51164
光源	LED6200_70_5150 x1 5150.0 lm
管理番号	K0141892(0)DB1
BZ分類	BZ6/0.7/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	7%	床	10%				10%				10%				10%				0%	
下方光束	93%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	53	41	32	27	52	40	32	27	48	38	31	26	45	36	30	25	23
	中	0.6	0.8	63	51	43	37	61	50	42	36	57	48	41	36	54	46	40	35	32
	否	0.56	1.0	70	58	50	44	68	57	49	43	64	55	48	42	60	52	46	42	38
			1.25	76	65	57	51	73	64	57	51	69	61	55	50	65	58	53	48	45
下方投影面積		cm <sup>2</sup>	1.5	80	70	63	57	78	69	62	56	73	66	60	55	69	63	58	54	50
等価発光面積		cm <sup>2</sup>	2.0	86	78	71	66	83	76	70	65	79	73	67	63	75	70	65	61	57
取付高さ	器具間隔最大限		2.5	90	82	77	71	87	81	75	70	83	77	73	69	79	74	70	67	63
	横方向 (A)	縦方向 (B)	3.0	92	86	81	76	90	84	79	75	85	81	76	73	81	77	74	71	66
H <sub>m</sub>	1.39H <sub>m</sub>	1.39H <sub>m</sub>	4.0	95	90	86	82	93	89	85	81	89	85	82	78	85	82	79	76	72
			5.0	98	93	90	86	95	91	88	85	91	88	85	82	87	84	82	80	75
			7.0	100	97	94	91	98	95	92	90	94	91	89	87	90	88	86	84	79
			10.0	102	100	97	95	100	98	96	94	96	94	92	91	92	90	89	88	83

