

屋内照明器具特性

品番 (品名)	L G W C 8 0 3 6 0														
光源	LED2700_70_515 x1 515.0 l m														
管理番号	K0171392 (0) DB 1														
B Z 分類	BZ9 / 0.9 / BZ8														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %			
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
		床	10 %				10 %				10 %				10 %				0 %			
上方光束	51 %	室指数																				
下方光束	49 %	照明率 (X0.01)																				
		Z C M																				
保守率	良 中 否	0.63	0.6	0.56	0.6	45	32	24	19	41	29	22	17	33	24	19	14	26	20	15	11	6
		0.6	0.8	53	41	32	26	48	37	30	24	40	31	25	20	32	25	20	17	10		
		1.0	1.0	59	47	39	32	54	43	36	30	44	36	30	25	35	29	24	21	13		
		0.56	1.25	64	54	45	39	59	49	42	36	48	41	35	30	39	33	29	25	16		
下方投影面積	c m ²	1.5	69	58	50	44	63	54	47	41	52	45	39	34	42	36	32	28	18			
		2.0	74	65	58	52	68	60	54	48	56	50	45	41	46	41	37	34	22			
取付高さ	器具間隔最大限		2.5	78	70	63	58	72	65	59	54	60	54	50	45	48	44	41	38	25		
	横方向 (A)	縦方向 (B)	3.0	80	73	67	62	74	68	62	58	62	57	53	49	51	47	44	41	27		
H m	1.62 H m	1.86 H m	4.0	84	78	73	68	77	72	68	64	65	61	57	54	53	50	48	45	31		
			5.0	86	81	77	73	80	75	71	68	67	64	60	58	55	53	50	48	33		
			7.0	89	85	81	78	82	79	76	73	70	67	64	62	58	56	54	52	36		
			10.0	91	88	85	83	84	82	79	77	72	70	68	66	60	58	57	55	39		

