

屋内照明器具特性	
品番 (品名)	XND2006WCK
光源	LED3500_85_1545 x1 1545.0lm
管理番号	K0176480 (0) DB1
BZ分類	BZ1

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C		M
下方光束		100 %																							
保守率		良	0.81	0.6	79	72	67	64	78	72	67	64	77	71	67	64	75	70	66	64	62				
		中	0.77	0.8	87	80	76	73	86	80	76	73	84	79	75	73	83	78	75	72	71				
		否	0.68	1.0	91	86	82	79	90	85	81	79	89	84	81	78	87	83	80	78	76				
				1.25	95	90	87	84	94	90	86	83	92	88	85	83	90	87	85	82	81				
下方投影面積		c m ²	1.5	97	93	90	87	96	92	89	87	94	91	88	86	93	90	88	86	84					
等価発光面積			c m ²	2.0	100	97	94	92	99	96	94	91	97	95	92	90	95	93	91	90	88				
取付	器具間隔最大限		2.5	102	99	97	95	101	98	96	94	99	97	95	93	97	95	94	92	90					
高さ	横方向 (A)		縦方向 (B)	3.0	103	101	99	97	102	100	98	96	100	98	97	95	98	97	95	94	92				
H m	0.73 H m		0.73 H m	4.0	105	103	101	100	104	102	100	99	101	100	99	97	99	98	97	96	94				
				5.0	106	104	103	101	104	103	102	100	102	101	100	99	100	99	98	97	95				
				7.0	107	105	104	103	105	104	103	102	103	102	101	101	100	100	99	97					
				10.0	107	106	106	105	106	105	105	104	104	103	103	102	102	101	101	100	98				

