

屋内照明器具特性	
品番 (品名)	L G W 8 5 0 8 1 Y F
光源	LDA5 L - D - G - E17 / S / Z4 ×1 440.0 l m
管理番号	K0175938 (0) DR 1
BZ分類	BZ7 / 4.5 / BZ6 / 6.0 / BZ7 / 8.5 / BZ6

器具効率	69 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	33 %		床	10 %				10 %				10 %				10 %				0 %
下方光束	36 %		室指数	照明率 (X0.01)																Z C M
保守率	良 0.63	0.6 中 否 0.56	0.6	3.2	2.4	1.8	1.4	2.9	2.2	1.7	1.4	2.5	1.9	1.5	1.2	2.0	1.5	1.2	1.0	6
	0.8		3.8	3.0	2.4	2.0	3.5	2.8	2.2	1.9	2.9	2.3	1.9	1.6	2.4	2.0	1.6	1.4	9	
	1.0		4.2	3.4	2.9	2.4	3.9	3.2	2.7	2.3	3.2	2.7	2.3	2.0	2.7	2.3	1.9	1.7	1.2	
	1.25		4.6	3.9	3.3	2.9	4.2	3.6	3.1	2.7	3.5	3.0	2.7	2.3	2.9	2.5	2.2	2.0	1.4	
下方投影面積	cm ²	1.5	4.8	4.2	3.7	3.2	4.5	3.9	3.4	3.0	3.8	3.3	2.9	2.6	3.1	2.8	2.5	2.2	1.6	
		2.0	5.2	4.7	4.2	3.8	4.8	4.3	3.9	3.5	4.1	3.7	3.4	3.1	3.4	3.1	2.8	2.6	1.9	
取付高さ	器具間隔最大限		2.5	5.5	5.0	4.5	4.2	5.1	4.6	4.2	3.9	4.3	4.0	3.7	3.4	3.6	3.3	3.1	2.9	2.1
	横方向 (A)	縦方向 (B)	3.0	5.7	5.2	4.8	4.5	5.2	4.8	4.5	4.2	4.5	4.1	3.9	3.6	3.7	3.5	3.3	3.1	2.2
H m	1.29 H m	1.72 H m	4.0	5.9	5.5	5.2	4.9	5.5	5.1	4.8	4.6	4.7	4.4	4.2	4.0	3.9	3.7	3.5	3.4	2.5
			5.0	6.0	5.7	5.4	5.2	5.6	5.3	5.1	4.8	4.8	4.6	4.4	4.2	4.0	3.9	3.7	3.6	2.6
			7.0	6.2	6.0	5.7	5.5	5.8	5.6	5.4	5.2	5.0	4.8	4.6	4.5	4.2	4.1	3.9	3.8	2.8
			10.0	6.3	6.2	6.0	5.8	5.9	5.7	5.6	5.4	5.1	5.0	4.8	4.7	4.3	4.2	4.1	4.0	3.0

