

# 屋内照明器具特性

品番 (品名)	L G W C 4 7 1 2 7									
光源	LLD2000LCB1 ×1					531.0 lm				
管理番号	K0176341(0)DR1									
BZ分類	BZ3/0.9/BZ2/4.5/BZ3/6.0/BZ2									

器具効率	68%	天井	80%				70%				50%				30%				0%																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																				
		床	10%				10%				10%				10%				0%																																				
上方光束	0%	室指数																		照明率 ( X0.01 )																		ZCM																	
下方光束	68%																																																						
保守率	良 中 否	0.63	0.6	0.56	0.6	4.4	3.7	3.2	2.9	4.3	3.6	3.2	2.9	4.2	3.6	3.2	2.9	4.0	3.5	3.2	2.9	2.8																																	
		0.6	0.8	5.1	4.5	4.0	3.7	5.0	4.4	4.0	3.7	4.8	4.3	4.0	3.7	4.7	4.3	3.9	3.7	3.5																																			
		1.0	1.0	5.5	5.0	4.6	4.2	5.4	4.9	4.5	4.2	5.3	4.8	4.5	4.2	5.1	4.7	4.4	4.2	4.1																																			
		0.56	1.25	5.9	5.4	5.0	4.7	5.8	5.3	5.0	4.7	5.6	5.2	4.9	4.7	5.5	5.1	4.9	4.6	4.5																																			
下方投影面積	c m <sup>2</sup>	1.5	6.1	5.7	5.3	5.1	6.0	5.6	5.3	5.0	5.9	5.5	5.2	5.0	5.7	5.4	5.2	5.0	4.8																																				
		2.0	6.4	6.1	5.8	5.5	6.3	6.0	5.7	5.5	6.2	5.9	5.6	5.4	6.0	5.8	5.6	5.4	5.3																																				
取付高さ	器具間隔最大限		2.5	6.6	6.3	6.1	5.8	6.5	6.2	6.0	5.8	6.4	6.1	5.9	5.7	6.2	6.0	5.8	5.7	5.5																																			
	横方向 (A)	縦方向 (B)	3.0	6.7	6.5	6.3	6.1	6.6	6.4	6.2	6.0	6.5	6.3	6.1	5.9	6.3	6.2	6.0	5.9	5.7																																			
H m	1.17 H m	1.17 H m	4.0	6.9	6.7	6.5	6.3	6.8	6.6	6.4	6.3	6.6	6.5	6.3	6.2	6.5	6.3	6.2	6.1	6.0																																			
			5.0	7.0	6.8	6.7	6.5	6.9	6.7	6.6	6.5	6.7	6.6	6.5	6.4	6.6	6.5	6.4	6.3	6.1																																			
			7.0	7.1	7.0	6.8	6.7	7.0	6.9	6.8	6.7	6.8	6.7	6.7	6.6	6.7	6.6	6.5	6.5	6.3																																			
			10.0	7.2	7.1	7.0	6.9	7.1	7.0	6.9	6.8	6.9	6.8	6.8	6.7	6.8	6.7	6.7	6.6	6.4																																			

