

屋内照明器具特性	
品番 (品名)	XND2 5 0 8 WYK
光源	LED2700_85_2240 x1 2240.0 lm
管理番号	K0176484 (0) DB 1
B Z 分類	BZ1

器具効率		1 0 1 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		1 0 1 %																				
保守率		良 中 否	0 . 6	7 7	7 0	6 5	6 1	7 6	6 9	6 4	6 1	7 5	6 8	6 4	6 1	7 3	6 8	6 4	6 1	6 0		
			0 . 7 7	0 . 8	8 5	7 8	7 4	7 0	8 4	7 8	7 3	7 0	8 2	7 7	7 3	7 0	8 1	7 6	7 2	7 0	6 8	
			1 . 0	9 0	8 4	8 0	7 6	8 9	8 3	7 9	7 6	8 7	8 2	7 9	7 6	8 5	8 1	7 8	7 5	7 4		
			0 . 6 8	1 . 2 5	9 4	8 9	8 5	8 2	9 3	8 8	8 4	8 1	9 1	8 7	8 4	8 1	8 9	8 6	8 3	8 0	7 9	
下方投影面積		c m ²	1 . 5	9 7	9 2	8 8	8 5	9 6	9 1	8 8	8 5	9 3	9 0	8 7	8 4	9 2	8 8	8 6	8 4	8 2		
			2 . 0	1 0 0	9 6	9 3	9 0	9 9	9 5	9 2	9 0	9 7	9 4	9 1	8 9	9 5	9 2	9 0	8 8	8 6		
等価発光面積	c m ²	2 . 5	1 0 2	9 9	9 6	9 4	1 0 1	9 8	9 5	9 3	9 8	9 6	9 4	9 2	9 6	9 4	9 3	9 1	8 9			
		3 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	9 9	9 7	9 5	1 0 0	9 8	9 6	9 4	9 8	9 6	9 4	9 3	9 1			
H m	0 . 7 4 H m	0 . 7 4 H m	4 . 0	1 0 5	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	1 0 0	9 8	9 7	9 9	9 8	9 7	9 6	9 3		
			5 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 1	1 0 0	1 0 2	1 0 1	1 0 0	9 8	1 0 0	9 9	9 8	9 7	9 5		
			7 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 9	9 6		
			1 0 . 0	1 0 7	1 0 6	1 0 5	1 0 5	1 0 6	1 0 5	1 0 4	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	9 7		

