

# 屋内照明器具特性

品番 (品名)	LGD3120N	
光源	LED5000_70_805 ×1	805.0 1m
管理番号	K0160343(0)D 1	
BZ分類	BZ1	

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束		0%	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	100%	床	10%				10%				10%				10%				0%	
室指数	照明率 ( X0.01 )																			ZCM
保守率	良	0.67	0.6	85	79	76	73	85	79	76	73	83	79	75	73	82	78	75	73	72
	中	0.63	0.8	90	85	82	79	90	85	81	79	88	84	81	79	87	83	81	79	77
	否	0.56	1.0	94	89	86	83	93	89	85	83	91	88	85	83	90	87	84	82	81
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	97	93	89	87	96	92	89	87	94	91	88	86	92	90	87	86	84
			1.5	99	95	92	90	98	94	92	89	96	93	91	89	94	92	90	88	87
取付高さ	器具間隔最大限		2.5	103	100	98	96	102	99	97	96	100	98	96	95	98	96	95	94	92
	横方向 (A)	縦方向 (B)	3.0	104	101	100	98	103	101	99	97	101	99	97	96	99	97	96	95	93
Hm	0.35Hm	0.36Hm	4.0	105	103	102	100	104	102	101	100	102	100	99	98	100	99	98	97	95
			5.0	106	104	103	102	105	103	102	101	102	101	101	100	100	100	99	98	96
			7.0	106	106	105	104	105	105	104	103	103	103	102	101	101	101	100	100	97
			10.0	107	107	106	105	106	105	105	104	104	103	103	103	102	101	101	101	98

