

屋内照明器具特性	
品番 (品名)	XAD1129V
光源	LLD2020VCE1 ×1 460.0 lm
管理番号	K0187671 (1) DR1
BZ分類	BZ1

器具効率	8 7 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
			壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
			床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束	8 7 %	室指数	照明率 (X 0 . 0 1)																		Z C M	
下方光束																						
保守率	良	0 . 6 7	0 . 6	7 6	7 1	6 8	6 6	7 5	7 1	6 8	6 6	7 4	7 0	6 8	6 6	7 3	7 0	6 8	6 6	6 5		
	中	0 . 6 3	0 . 8	8 0	7 6	7 4	7 2	8 0	7 6	7 3	7 2	7 9	7 5	7 3	7 1	7 8	7 5	7 3	7 1	7 0		
	否	0 . 5 6	1 . 0	8 3	8 0	7 7	7 5	8 3	7 9	7 7	7 5	8 1	7 8	7 6	7 5	8 0	7 8	7 6	7 4	7 3		
	1 . 2 5		8 5	8 2	8 0	7 8	8 5	8 2	8 0	7 8	8 3	8 1	7 9	7 7	8 2	8 0	7 8	7 7	7 6			
下方投影面積	c m ²	1 . 5	8 7	8 4	8 2	8 0	8 6	8 4	8 2	8 0	8 5	8 2	8 1	7 9	8 3	8 1	8 0	7 9	7 8			
等価発光面積		c m ²	2 . 0	8 9	8 6	8 5	8 3	8 8	8 6	8 4	8 3	8 6	8 5	8 3	8 2	8 5	8 3	8 2	8 1	8 0		
2 . 5		9 0	8 8	8 6	8 5	8 9	8 7	8 6	8 4	8 7	8 6	8 5	8 4	8 6	8 5	8 4	8 3	8 1				
取付 高さ	器具間隔最大限		3 . 0	9 1	8 9	8 7	8 6	9 0	8 8	8 7	8 6	8 8	8 7	8 6	8 5	8 6	8 5	8 4	8 4	8 2		
	横方向 (A)	縦方向 (B)	4 . 0	9 1	9 0	8 9	8 8	9 1	8 9	8 8	8 7	8 9	8 8	8 7	8 6	8 7	8 6	8 6	8 5	8 3		
H m	0 . 4 3 H m	0 . 4 3 H m	5 . 0	9 2	9 1	9 0	8 9	9 1	9 0	8 9	8 8	8 9	8 8	8 8	8 7	8 8	8 7	8 6	8 6	8 4		
			7 . 0	9 3	9 2	9 1	9 0	9 2	9 1	9 0	9 0	9 0	8 9	8 9	8 8	8 8	8 8	8 7	8 7	8 5		
			1 0 . 0	9 3	9 2	9 2	9 1	9 2	9 2	9 1	9 1	9 0	9 0	8 9	8 9	8 8	8 8	8 8	8 7	8 5		

