

屋内照明器具特性	
品番 (品名)	XAD1129N
光源	LLD2020NCE1 ×1 460.0 lm
管理番号	K0187671 (1) DR1
BZ分類	BZ1

器具効率		87 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		87 %																						
保守率		良	0.67	0.6	76	71	68	66	75	71	68	66	74	70	68	66	73	70	68	66	65			
		中	0.63	0.8	80	76	74	72	80	76	73	72	79	75	73	71	78	75	73	71	70			
		否	0.56	1.0	83	80	77	75	83	79	77	75	81	78	76	75	80	78	76	74	73			
		0.56	1.25	85	82	80	78	85	82	80	78	83	81	79	77	82	80	78	77	76				
下方投影面積		c m ²	1.25	85	82	80	78	85	82	80	78	83	81	79	77	82	80	78	77	76				
等価発光面積			c m ²	1.5	87	84	82	80	86	84	82	80	85	82	81	79	83	81	80	79	78			
			2.0	89	86	85	83	88	86	84	83	86	85	83	82	85	83	82	81	80				
取付 高さ	器具間隔最大限		2.5	90	88	86	85	89	87	86	84	87	86	85	84	86	85	84	83	81				
	横方向 (A)		縦方向 (B)	3.0	91	89	87	86	90	88	87	86	88	87	86	85	86	85	84	84	82			
H m	0.43 H m	0.43 H m	4.0	91	90	89	88	91	89	88	87	89	88	87	86	87	86	86	85	83				
			5.0	92	91	90	89	91	90	89	88	89	88	88	87	88	87	86	86	84				
			7.0	93	92	91	90	92	91	90	90	90	89	89	88	88	88	87	87	85				
			10.0	93	92	92	91	92	92	91	91	90	90	89	89	88	88	88	87	85				

