

屋内照明器具特性	
品番 (品名)	LGB52604
光源	LED5000_70_1760 ×1 1760.0 lm
管理番号	K0189468 (0) D 1
BZ分類	BZ5

器具効率		100 % 上方光束 10 % 下方光束 90 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) ZCM															
保守率		良 中 否	0.63	0.6	54	41	33	28	52	40	33	28	49	39	32	27	46	37	31	26	24	
			0.6	0.8	63	51	43	37	61	50	43	37	57	48	41	36	54	46	40	35	32	
			0.56	1.0	70	58	50	44	67	57	49	44	63	54	48	43	59	52	46	41	38	
				1.25	75	65	57	51	73	64	56	51	68	60	54	49	64	58	52	48	44	
下方投影面積		cm ²	1.5	80	70	63	57	77	68	61	56	72	65	59	54	68	62	57	53	49		
			2.0	85	77	70	65	83	75	69	64	78	71	66	62	73	68	64	60	55		
取付 高さ	器具間隔最大限		2.5	89	82	76	70	86	80	74	69	81	76	71	67	77	72	68	65	60		
	横方向 (A)	縦方向 (B)	3.0	91	85	80	75	89	83	78	74	84	79	75	71	79	75	72	69	64		
H m	1.27 H m	1.27 H m	4.0	95	89	85	81	92	87	83	79	87	83	80	76	83	79	76	74	69		
			5.0	97	92	88	85	94	90	86	83	89	86	83	80	85	82	79	77	72		
			7.0	99	96	93	90	97	93	91	88	92	89	87	85	87	85	83	81	76		
			10.0	101	98	96	94	99	96	94	92	94	92	90	88	90	88	86	85	80		

