

屋内照明器具特性	
品番 (品名)	LGB52624
光源	LED5000_70_2550 ×1 2550.0 lm
管理番号	K0189468 (0) D 1
BZ分類	BZ5

器具効率		1 0 0 % 上方光束 1 0 % 下方光束 9 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
			室指数	照明率 (X 0 . 0 1)																Z C M	
保守率		良 中 否	0 . 6 3	0 . 6	5 4	4 1	3 3	2 8	5 2	4 0	3 3	2 8	4 9	3 9	3 2	2 7	4 6	3 7	3 1	2 6	2 4
			0 . 6	0 . 8	6 3	5 1	4 3	3 7	6 1	5 0	4 3	3 7	5 7	4 8	4 1	3 6	5 4	4 6	4 0	3 5	3 2
			0 . 5 6	1 . 0	7 0	5 8	5 0	4 4	6 7	5 7	4 9	4 4	6 3	5 4	4 8	4 3	5 9	5 2	4 6	4 1	3 8
				1 . 2 5	7 5	6 5	5 7	5 1	7 3	6 4	5 6	5 1	6 8	6 0	5 4	4 9	6 4	5 8	5 2	4 8	4 4
下方投影面積		c m ²	1 . 5	8 0	7 0	6 3	5 7	7 7	6 8	6 1	5 6	7 2	6 5	5 9	5 4	6 8	6 2	5 7	5 3	4 9	
等価発光面積			c m ²	2 . 0	8 5	7 7	7 0	6 5	8 3	7 5	6 9	6 4	7 8	7 1	6 6	6 2	7 3	6 8	6 4	6 0	5 5
				2 . 5	8 9	8 2	7 6	7 0	8 6	8 0	7 4	6 9	8 1	7 6	7 1	6 7	7 7	7 2	6 8	6 5	6 0
取付 高さ	器具間隔最大限		3 . 0	9 1	8 5	8 0	7 5	8 9	8 3	7 8	7 4	8 4	7 9	7 5	7 1	7 9	7 5	7 2	6 9	6 4	
	横方向 (A)																				縦方向 (B)
H m	1 . 2 7 H m	1 . 2 7 H m	4 . 0	9 5	8 9	8 5	8 1	9 2	8 7	8 3	7 9	8 7	8 3	8 0	7 6	8 3	7 9	7 6	7 4	6 9	
			5 . 0	9 7	9 2	8 8	8 5	9 4	9 0	8 6	8 3	8 9	8 6	8 3	8 0	8 5	8 2	7 9	7 7	7 2	
			7 . 0	9 9	9 6	9 3	9 0	9 7	9 3	9 1	8 8	9 2	8 9	8 7	8 5	8 7	8 5	8 3	8 1	7 6	
			1 0 . 0	1 0 1	9 8	9 6	9 4	9 9	9 6	9 4	9 2	9 4	9 2	9 0	8 8	9 0	8 8	8 6	8 5	8 0	

