

屋内照明器具特性	
品番 (品名)	L G B 5 2 6 3 8
光源	LED3500_70_2230 ×1 2230.0 lm
管理番号	K0189500 (0) D 1
B Z 分類	B Z 5

器具効率		1 0 0 % 上方光束 6 % 下方光束 9 4 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
				室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 3	0 . 6	0 . 5 6	0 . 6	5 4	4 2	3 4	2 8	5 3	4 1	3 3	2 8	5 0	3 9	3 2	2 7	4 7	3 8	3 2	2 7	2 5		
			0 . 6	0 . 8	0 . 6	0 . 8	6 4	5 2	4 4	3 8	6 2	5 1	4 3	3 7	5 8	4 9	4 2	3 7	5 5	4 7	4 1	3 6	3 3		
			0 . 5 6	1 . 0	0 . 5 6	1 . 0	7 0	5 9	5 1	4 5	6 8	5 8	5 0	4 4	6 4	5 5	4 9	4 3	6 1	5 3	4 7	4 3	4 0		
			0 . 5 6	1 . 2 5	0 . 5 6	1 . 2 5	7 6	6 6	5 8	5 2	7 4	6 4	5 7	5 1	7 0	6 2	5 5	5 0	6 6	5 9	5 4	4 9	4 6		
下方投影面積 等価発光面積		c m ² c m ²	0 . 6 3	0 . 6	0 . 5 6	0 . 6	8 0	7 1	6 3	5 7	7 8	6 9	6 2	5 6	7 4	6 6	6 0	5 5	7 0	6 4	5 8	5 4	5 1		
			0 . 6	2 . 0	0 . 6	2 . 0	8 6	7 8	7 1	6 5	8 3	7 6	7 0	6 4	7 9	7 3	6 7	6 3	7 5	7 0	6 5	6 1	5 8		
			0 . 5 6	2 . 5	0 . 5 6	2 . 5	8 9	8 2	7 6	7 1	8 7	8 0	7 5	7 0	8 3	7 7	7 2	6 8	7 9	7 4	7 0	6 6	6 3		
			0 . 5 6	3 . 0	0 . 5 6	3 . 0	9 2	8 6	8 0	7 5	9 0	8 4	7 9	7 4	8 5	8 0	7 6	7 2	8 1	7 7	7 4	7 0	6 6		
H m	1 . 2 7 H m	1 . 2 7 H m	4 . 0	9 5	9 0	8 5	8 1	9 3	8 8	8 4	8 0	8 9	8 5	8 1	7 8	8 5	8 2	7 8	7 6	7 2					
			5 . 0	9 7	9 3	8 9	8 5	9 5	9 1	8 7	8 4	9 1	8 8	8 4	8 2	8 7	8 4	8 2	7 9	7 5					
			7 . 0	1 0 0	9 6	9 3	9 0	9 8	9 5	9 2	8 9	9 4	9 1	8 9	8 6	9 0	8 8	8 6	8 4	7 9					
			1 0 . 0	1 0 2	9 9	9 7	9 4	1 0 0	9 7	9 5	9 3	9 6	9 4	9 2	9 0	9 2	9 0	8 9	8 7	8 3					

