

屋内照明器具特性	
品番 (品名)	L G B C 8 1 0 2 4
光源	LED5000_70_1720 ×1 1720.0 lm
管理番号	K0189502 (0) D 1
B Z 分類	BZ5 / 8.5 / BZ6

器具効率		100 % 上方光束 10 % 下方光束 90 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) Z C M															
保守率		良 中 否	0.63	0.6	54	41	33	28	52	40	33	28	48	38	32	27	45	37	31	26	24	
			0.6	0.8	63	51	43	37	61	50	42	37	57	48	41	36	53	45	39	35	32	
			0.56	1.0	70	58	50	44	67	57	49	44	63	54	48	42	59	51	46	41	38	
			1.25	75	65	57	51	73	63	56	50	68	60	54	49	64	57	52	48	44		
下方投影面積		c m ²	1.5	79	70	62	57	77	68	61	56	72	65	59	54	68	62	57	52	48		
等価発光面積			c m ²	2.0	85	77	70	65	82	75	69	64	78	71	66	62	73	68	63	59		
取付高さ				器具間隔最大限		2.5	89	81	75	70	86	79	74	69	81	76	71	67	76	72	68	
H m		1.27 H m	縦方向 (B)	3.0	91	85	79	75	89	83	78	73	84	79	75	71	79	75	71	68		
H m		1.27 H m		4.0	94	89	85	81	92	87	83	79	87	83	79	76	82	79	76	73		
				5.0	96	92	88	85	94	90	86	83	89	86	83	80	84	82	79	77		
				7.0	99	96	92	90	96	93	90	88	92	89	87	84	87	85	83	81		
				10.0	101	98	96	94	98	96	94	92	94	92	90	88	89	88	86	85		

