

屋内照明器具特性	
品番 (品名)	L G B C 8 1 0 3 4
光源	LED5000_70_1625 ×1 1625.0 lm
管理番号	K0189500 (0) D 1
B Z 分類	B Z 5

器具効率		100 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %					10 %					10 %					10 %					0 %
						室指数	照明率 (X0.01) Z C M																			
保守率		良 中 否	0.63	0.6	0.56	0.6	54	42	34	28	53	41	33	28	50	39	32	27	47	38	32	27	25			
			0.6	0.8	64	52	44	38	62	51	43	37	58	49	42	37	55	47	41	36	33					
			0.56	1.0	70	59	51	45	68	58	50	44	64	55	49	43	61	53	47	43	40					
			0.56	1.25	76	66	58	52	74	64	57	51	70	62	55	50	66	59	54	49	46					
下方投影面積		c m ²	1.5	80	71	63	57	78	69	62	56	74	66	60	55	70	64	58	54	51						
等価発光面積			c m ²	2.0	86	78	71	65	83	76	70	64	79	73	67	63	75	70	65	61	58					
取付高さ	器具間隔最大限			2.5	89	82	76	71	87	80	75	70	83	77	72	68	79	74	70	66	63					
	横方向 (A)			縦方向 (B)	3.0	92	86	80	75	90	84	79	74	85	80	76	72	81	77	74	70	66				
H m	1.27 H m	1.27 H m		4.0	95	90	85	81	93	88	84	80	89	85	81	78	85	82	78	76	72					
			5.0	97	93	89	85	95	91	87	84	91	88	84	82	87	84	82	79	75						
			7.0	100	96	93	90	98	95	92	89	94	91	89	86	90	88	86	84	79						
			10.0	102	99	97	94	100	97	95	93	96	94	92	90	92	90	89	87	83						

