

屋内照明器具特性

品番 (品名)	LGD3200N														
光源	LED5000_70_820 x1					820.0 l m									
管理番号	K0148419 (0) DB 1														
BZ分類	BZ4 / 3.5 / BZ3														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	0 %	反射率	10 %				10 %				10 %				10 %				0 %	
下方光束	100 %		床	10 %				10 %				10 %				10 %				0 %
室指数	照明率 (X0.01)															ZCM				
保守率	良 中 否	0.67	0.6	59	47	40	35	58	47	40	35	55	46	39	34	53	45	39	34	32
		0.63	0.8	69	59	51	46	68	58	51	46	65	57	50	45	63	55	50	45	43
		0.56	1.0	76	66	59	54	75	65	59	54	72	64	58	53	69	62	57	53	51
			1.25	82	73	67	62	81	73	66	61	78	71	65	61	75	69	64	61	58
下方投影面積	c m ²	1.5	86	78	72	67	85	78	72	67	82	76	71	67	79	74	70	66	64	
		2.0	92	85	80	76	90	84	80	75	88	83	78	75	85	81	77	74	72	
取付高さ	器具間隔最大限		2.5	95	90	85	81	94	89	85	81	91	87	83	80	88	85	82	79	77
	横方向 (A)	縦方向 (B)	3.0	97	93	89	85	96	92	88	85	93	90	87	84	91	88	85	83	80
H m	1.21 H m	1.21 H m	4.0	100	97	93	91	99	95	93	90	96	93	91	89	94	91	89	87	85
			5.0	102	99	96	94	100	98	95	93	98	96	94	92	95	94	92	90	88
			7.0	104	101	100	98	102	100	99	97	100	98	97	95	97	96	95	94	91
			10.0	105	103	102	101	104	102	101	100	101	100	99	98	99	98	97	96	93

