

# 屋内照明器具特性

品番 (品名)	LGD3200V									
光源	LED3500_70_800 x1					800.0 l m				
管理番号	K0148419 ( 0 ) DB 1									
BZ分類	BZ4 / 3.5 / BZ3									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	100 %	室指数	照明率 ( X0.01 )																ZCM	
保守率	良 中 否	0.67	0.6	5.9	4.7	4.0	3.5	5.8	4.7	4.0	3.5	5.5	4.6	3.9	3.4	5.3	4.5	3.9	3.4	3.2
		0.63	0.8	6.9	5.9	5.1	4.6	6.8	5.8	5.1	4.6	6.5	5.7	5.0	4.5	6.3	5.5	5.0	4.5	4.3
		0.56	1.0	7.6	6.6	5.9	5.4	7.5	6.5	5.9	5.4	7.2	6.4	5.8	5.3	6.9	6.2	5.7	5.3	5.1
			1.25	8.2	7.3	6.7	6.2	8.1	7.3	6.6	6.1	7.8	7.1	6.5	6.1	7.5	6.9	6.4	6.1	5.8
下方投影面積	c m <sup>2</sup>	1.5	8.6	7.8	7.2	6.7	8.5	7.8	7.2	6.7	8.2	7.6	7.1	6.7	7.9	7.4	7.0	6.6	6.4	
		2.0	9.2	8.5	8.0	7.6	9.0	8.4	8.0	7.5	8.8	8.3	7.8	7.5	8.5	8.1	7.7	7.4	7.2	
取付高さ	器具間隔最大限		2.5	9.5	9.0	8.5	8.1	9.4	8.9	8.5	8.1	9.1	8.7	8.3	8.0	8.8	8.5	8.2	7.9	7.7
	横方向 (A)	縦方向 (B)	3.0	9.7	9.3	8.9	8.5	9.6	9.2	8.8	8.5	9.3	9.0	8.7	8.4	9.1	8.8	8.5	8.3	8.0
H m	1.21 H m	1.21 H m	4.0	10.0	9.7	9.3	9.1	9.9	9.5	9.3	9.0	9.6	9.3	9.1	8.9	9.4	9.1	8.9	8.7	8.5
			5.0	10.2	9.9	9.6	9.4	10.0	9.8	9.5	9.3	9.8	9.6	9.4	9.2	9.5	9.4	9.2	9.0	8.8
			7.0	10.4	10.1	10.0	9.8	10.2	10.0	9.9	9.7	10.0	9.8	9.7	9.5	9.7	9.6	9.5	9.4	9.1
			10.0	10.5	10.3	10.2	10.1	10.4	10.2	10.1	10.0	10.1	10.0	9.9	9.8	9.9	9.8	9.7	9.6	9.3

