

屋内照明器具特性	
品番 (品名)	L G B 1 5 8 1 1
光源	LDG3 L / F 8 / C / B 2 × 1 3 0 0 . 0 l m
管理番号	K 0 1 7 8 6 5 2 (0) D B 1
B Z 分類	B Z 7

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		3 8 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		6 2 %																				
保守率		良 中 否	0 . 6 9	0 . 6	4 7	3 5	2 7	2 1	4 4	3 3	2 5	2 0	3 8	2 9	2 2	1 8	3 2	2 5	2 0	1 6	1 1	
			0 . 6 7	0 . 8	5 6	4 4	3 5	2 9	5 2	4 1	3 3	2 8	4 5	3 6	3 0	2 5	3 8	3 1	2 6	2 2	1 6	
			0 . 6 3	1 . 0	6 2	5 0	4 2	3 6	5 8	4 7	4 0	3 4	5 0	4 1	3 5	3 0	4 3	3 6	3 1	2 7	2 0	
				1 . 2 5	6 8	5 7	4 9	4 2	6 3	5 3	4 6	4 0	5 5	4 7	4 1	3 6	4 7	4 1	3 6	3 2	2 4	
下方投影面積		c m ²	1 . 5	7 2	6 2	5 4	4 8	6 7	5 8	5 1	4 5	5 8	5 1	4 5	4 0	5 0	4 4	3 9	3 6	2 7		
等価発光面積		c m ²	2 . 0	7 8	6 9	6 2	5 6	7 2	6 5	5 8	5 3	6 3	5 7	5 2	4 7	5 4	4 9	4 5	4 2	3 2		
取付 高さ	器具間隔最大限		2 . 5	8 1	7 3	6 7	6 1	7 6	6 9	6 3	5 8	6 6	6 1	5 6	5 2	5 7	5 3	4 9	4 6	3 6		
	横方向 (A)		縦方向 (B)	3 . 0	8 4	7 7	7 1	6 6	7 9	7 2	6 7	6 2	6 9	6 4	5 9	5 6	5 9	5 6	5 2	4 9	3 9	
H m	0 . 7 6 H m	0 . 7 6 H m	4 . 0	8 7	8 1	7 6	7 2	8 2	7 7	7 2	6 8	7 2	6 8	6 4	6 1	6 2	5 9	5 6	5 4	4 2		
			5 . 0	8 9	8 4	8 0	7 6	8 4	8 0	7 6	7 2	7 4	7 0	6 7	6 4	6 4	6 2	5 9	5 7	4 5		
			7 . 0	9 2	8 8	8 5	8 1	8 7	8 3	8 0	7 7	7 6	7 4	7 1	6 9	6 7	6 5	6 3	6 1	4 8		
			1 0 . 0	9 4	9 1	8 8	8 6	8 9	8 6	8 4	8 1	7 8	7 6	7 4	7 2	6 9	6 7	6 6	6 4	5 1		

