

屋内照明器具特性	
品番 (品名)	L G W8 5 2 2 1 B
光源	L L D 3 0 2 0 L C B 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 9 0 5 7 4 (0) D R 1
B Z 分類	B Z 1 0

器具効率		61 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.63	0.6	0.6	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	15.0	20.0					
			0.63	0.6	0.6	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	15.0	20.0					
			0.63	0.6	0.6	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	15.0	20.0					
			0.63	0.6	0.6	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	15.0	20.0					
下方投影面積		cm ²	1.25	3.8	3.1	2.5	2.1	3.5	2.8	2.3	1.9	2.8	2.3	1.9	1.6	2.2	1.8	1.5	1.3	7					
等価発光面積			cm ²	1.5	4.0	3.4	2.8	2.4	3.7	3.1	2.6	2.2	3.0	2.5	2.2	1.8	2.4	2.0	1.7	15					
					2.0	4.4	3.8	3.3	2.9	4.0	3.5	3.1	2.7	3.3	2.9	2.5	2.2	2.6	2.3	2.0	18				
						2.5	4.6	4.1	3.7	3.3	4.2	3.8	3.4	3.0	3.5	3.1	2.8	2.5	2.8	2.5	2.3	21			
横方向 (A)		縦方向 (B)				3.0	4.8	4.3	3.9	3.5	4.4	4.0	3.6	3.3	3.7	3.3	3.0	2.8	3.0	2.7	2.5	23			
H m			0.00 H m			1.71 H m	4.0	5.0	4.6	4.3	4.0	4.6	4.3	3.9	3.7	3.9	3.6	3.3	3.1	3.1	2.9	2.7	25		
								5.0	5.2	4.8	4.5	4.2	4.8	4.5	4.2	3.9	4.0	3.8	3.5	3.3	3.3	3.1	2.9	2.7	19
									7.0	5.4	5.1	4.8	4.6	5.0	4.7	4.5	4.3	4.2	4.0	3.8	3.6	3.4	3.3	3.1	3.0
										10.0	5.5	5.3	5.1	4.9	5.1	4.9	4.7	4.6	4.3	4.2	4.0	3.9	3.6	3.5	3.4

