

屋内照明器具特性	
品番 (品名)	L G W8 5 2 2 1 S
光源	L L D 3 0 2 0 L C B 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 9 0 5 7 4 (0) D R 1
B Z 分類	B Z 1 0

器具効率		61 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		30 %	室指数	照明率 (X0.01)																			Z	CM
下方光束		31 %																						
保守率		良 中 否	0.63	0.6	26	18	13	9	24	16	12	9	19	13	10	7	15	10	7	5	2			
			0.6	0.8	31	23	18	14	28	21	16	13	23	17	13	10	18	14	10	8	4			
			0.56	1.0	35	27	21	17	31	25	20	16	25	20	16	13	20	16	13	10	5			
			1.25	38	31	25	21	35	28	23	19	28	23	19	16	22	18	15	13	7				
下方投影面積		cm ²	1.5	40	34	28	24	37	31	26	22	30	25	22	18	24	20	17	15	9				
等価発光面積			cm ²	2.0	44	38	33	29	40	35	31	27	33	29	25	22	26	23	20	18	11			
取付 高さ	器具間隔最大限		2.5	46	41	37	33	42	38	34	30	35	31	28	25	28	25	23	21	13				
	横方向 (A)		縦方向 (B)		3.0	48	43	39	35	44	40	36	33	37	33	30	28	30	27	25	23	15		
H m	0.00 H m		1.71 H m		4.0	50	46	43	40	46	43	39	37	39	36	33	31	31	29	27	25	17		
				5.0	52	48	45	42	48	45	42	39	40	38	35	33	33	31	29	27	19			
				7.0	54	51	48	46	50	47	45	43	42	40	38	36	34	33	31	30	21			
				10.0	55	53	51	49	51	49	47	46	43	42	40	39	36	35	34	32	23			

