

屋内照明器具特性	
品番 (品名)	L G W8 5 2 2 1 S
光源	LLD2020LCE1 ×1 460.0 lm
管理番号	K0190576 (0) DR 1
B Z 分類	BZ10

器具効率		6 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束 下方光束		3 1 % 3 1 %	室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 3	0 . 6	0 . 6	0 . 5 6	0 . 6	2 6	1 8	1 3	1 0	2 4	1 7	1 2	9	1 9	1 4	1 0	7	1 5	1 1	8	5	2
			0 . 6	0 . 8	3 1	2 3	1 8	1 4	2 9	2 1	1 6	1 3	2 3	1 8	1 3	1 0	1 8	1 4	1 1	8	4			
			0 . 5 6	1 . 0	3 5	2 7	2 2	1 8	3 2	2 5	2 0	1 6	2 6	2 0	1 6	1 3	2 0	1 6	1 3	1 0	5			
			0 . 5 6	1 . 2 5	3 9	3 1	2 6	2 1	3 5	2 9	2 4	2 0	2 9	2 3	1 9	1 6	2 3	1 9	1 5	1 3	7			
下方投影面積		cm ²	1 . 5	4 1	3 4	2 9	2 5	3 7	3 1	2 7	2 3	3 1	2 6	2 2	1 9	2 4	2 1	1 8	1 5	9				
等価発光面積		cm ²	2 . 0	4 5	3 9	3 4	3 0	4 1	3 5	3 1	2 7	3 4	2 9	2 6	2 3	2 7	2 4	2 1	1 8	1 1				
取付 高さ	器具間隔最大限		2 . 5	4 7	4 2	3 7	3 3	4 3	3 8	3 4	3 1	3 6	3 2	2 9	2 6	2 9	2 6	2 3	2 1	1 3				
	横方向 (A)	縦方向 (B)	3 . 0	4 9	4 4	4 0	3 6	4 5	4 0	3 7	3 3	3 7	3 4	3 1	2 8	3 0	2 7	2 5	2 3	1 5				
H m	0 . 0 0 H m	1 . 7 1 H m	4 . 0	5 1	4 7	4 3	4 0	4 7	4 3	4 0	3 7	3 9	3 6	3 4	3 1	3 2	3 0	2 8	2 6	1 7				
			5 . 0	5 3	4 9	4 6	4 3	4 8	4 5	4 2	4 0	4 1	3 8	3 6	3 4	3 3	3 1	3 0	2 8	1 9				
			7 . 0	5 4	5 2	4 9	4 7	5 0	4 8	4 5	4 3	4 2	4 0	3 9	3 7	3 5	3 3	3 2	3 1	2 1				
			1 0 . 0	5 6	5 4	5 2	5 0	5 2	5 0	4 8	4 6	4 4	4 2	4 1	3 9	3 6	3 5	3 4	3 3	2 3				

